	n nodaot ana bompany rao	lanoadon	
Product Name: Company Name:	Jasco VM&P Naphtha W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100	
Web site address:	www.wmbarr.com		
Emergency Contact: Information:	3E 24 Hour Emergency Contact (800)451-8346 W.M. Barr Customer Service (800)398-3892		
Synonyms:	GJVM46, CJVM46, GJVM190		

1. Product and Company Identification

2. Hazards Identification

Flammable Liquids, Category 2 Germ Cell Mutagenicity, Category 1B Aspiration Toxicity, Category 1

 \wedge

GHS Signal Word:	Danger
GHS Hazard Phrases:	H225: Highly flammable liquid and vapor.
	H340: May cause genetic defects.
	H304: May be fatal if swallowed and enters airways.
GHS Precaution Phrases:	P233: Keep container tightly closed.
	P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P240: Ground/bond container and receiving equipment.
	P241: Use explosion-proof electrical/ventilating/lighting equipment.
	P243: Take precautionary measures against static discharge. P242: Use only non-sparking tools.
	P242. Ose only non-sparking tools. P201: Obtain special instructions before use.
	P202: Do not handle until all safety precautions have been read and understood.
GHS Response Phrases:	P370+378: In case of fire, use dry chemical to extinguish.
	P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated
	clothing. Rinse skin with water/shower.
	P308+313: IF exposed or concerned: Get medical attention/advice.
	P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P331: Do NOT induce vomiting.
GHS Storage and Disposal	P403+235: Store in cool/well-ventilated place.
Phrases:	P501: Dispose of contents/container according to local, state and federal regulations.
	P405: Store locked up.
Hazard Rating System:	HEALTH * 2
	FLAMMABILITY 3
	PHYSICAL 0 Health
HMIS:	PPE NFPA: Special Hazard
OSHA Regulatory Status:	This material is classified as hazardous under OSHA regulations.

Page: 2 Printed: 09/15/2014 Revision: 09/05/2014 Supersedes Revision: 04/08/2013

Potential Health Effects (Acute and Chronic):

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness, headache, irritation of respiratory tract, weakness, drowsiness, depression of central nervous system, and watering of eyes. Severe overexposure may cause unconsciousness, anesthesia, irregular heartbeat, and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

This product is a skin irritant. It may be absorbed through the skin. It may cause irritation, dermatitis, drying of skin, and numbness in fingers and arms. May increase severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. It may cause irritation, redness, stinging, tearing, excessive swelling of the conjunctiva; and or excessive blinking.

Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. May cause nausea, vomiting, gastrointestinal irritation, or diarrhea.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. May cause skin irritation, permanent central nervous system changes, kidney damage, and liver damage.

Medical Conditions Generally Diseases of the skin, respiratory system, liver, central nervous system and kidneys. **Aggravated By Exposure:**

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)		Concentration		
64742-49-0	Hydrotreated light naphtha		95.0 -100.0 %		
		4. First Aid	d Measures		
artificial respiration unt		If user experiences breathing	g difficulty, move to air free of vapors. Administer oxygen or lical assistance can be rendered.		
			ately wash with soap and water.		
		Eye Contact: Immediately flush with water at least 15 minutes, then get	, remove any contact lenses, continue flushing with water for medical attention.		
		Ingestion: Do not induce vomiting. Cal	l you local poison control center, hospital emergency room,		
		or physician immediately for			
Signs and Sy Exposure:	mptoms Of	Primary Routes of Exposure Inhalation; ingestion; and de			
Note to Phys	ician:	Call your local poison contro	ol center for further information.		

5. Fire Fighting Measures

	OSHA Class IB		
Flash Pt:	69.00 F Method Used: TAG Closed Cup		
Explosive Limits:	LEL: 0.9 UEL: 6.7		
Autoignition Pt:	47.50 F		
Suitable Extinguishing Media	a:Use carbon dioxide, dry powder, or foam.		
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spay to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.		
Flammable Properties and Hazards:	No data available.		
	6. Accidental Release Measures		
Steps To Be Taken In Case Material Is Released Or Spilled:	Cleanup: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area.		
	Small Spills: Take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.		
	Large Spills: Dike far ahead of spill for later disposal.		
	7. Handling and Storage		
Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.		
Precautions To Be Taken in Storing:	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.		
	0. Even a suma Canaturala /Dana a nal Durata atian		

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name		OSHA TWA	ACGIH TWA	Other Limits
64742-49-0	Hydrotreated light	t naphtha	No data.	No data.	No data.
Respiratory (Specify Typ	• •	ventilation under er appropriate TLV. F properly maintained	ed work place and other reg ngineered air control system for occasional use, where e d and properly fitted NIOSH sk does not provided protec	ns designed to prevent ex ingineered air control is n approved respirator for c	ceeding ot feasible, use
Eye Protection	on:		emical goggles or face shiel ct, irritation, or injury. Conta cals.		
Protective G	loves:	•	gloves. Gloves contamina othing that becomes soiled	•	e discarded.
Other Protec	tive Clothing:		n methods can dictate the us impermeable aprons, etc.,	•	e safety

Engineering Controls (Ventilation etc.):	Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms, or small enclosed areas. Whenever possible, use outdoors in an open area. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering Stop ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, then do not use this product. A dust mask does not provide protection against vapors.
Work/Hygienic/Maintenance Practices:	A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

9. Physical and Chemical Properties

Physical States:	[]Gas [X]Liquid []Solid		
Appearance and Odor:	Transparent, colorless		
	Hydrocarbon solvent odor		
Melting Point:	No data.		
Boiling Point:	264.00 F - 291.00 F		
Autoignition Pt:	47.50 F		
Flash Pt:	69.00 F Method Used: TAG Closed Cup		
Explosive Limits:	LEL: 0.9 UEL: 6.7		
Specific Gravity (Water = 1):	0.76		
Bulk density:	6.34 LB/GA		
Vapor Pressure (vs. Air or mm Hg):	11 MM HG at 20.0 C		
Vapor Density (vs. Air = 1):	4 Air = 1		
Evaporation Rate:	No data.		
Solubility in Water:	< 0.1% w/w		
Percent Volatile:	99.999 % by weight.		
VOC / Volume:	762.0000 G/L		
	10. Stability and Reactivity		
Stability:	Unstable [] Stable [X]		
Conditions To Avoid - Instability:	No data available.		
Incompatibility - Materials To Avoid:	Incompatible with strong oxidizing agents.		
Hazardous Decomposition O Byproducts:	r Decomposition may produce carbon monoxide and carbon dioxide.		
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]		
Conditions To Avoid - Hazardous Reactions:	No data available.		

11. Toxicological Information

		11.1		mation			
tract irritation. Studies on laboratory animals irritation after repeated or prolonged contact spirits to the skin can produce defatting derr animals. The most common effects observe histological changes consistent with á2ì-glob			nimals have ontact. Rep og dermatitis oserved in r 2ì-globulin humans, a ot useful in a nstrated eff le changes e effects ha ults to hum	rmatitis and kidney damage in laboratory ed in repeated dose toxicity studies are obulin mediated renal effect in male rats. ans, any effects associated with á2ì-globulin eful in assessing human risk. In addition, ted effects in liver function as well as anges following repeated exposures to ects have not been dose-related. The			
Chronic Toxic Effects:	-		n 3 potential health effe	CIS			
CAS #	Hazardous Com	ponents (Chemic	al Name)	NTP	IARC	ACGIH	OSHA
64742-49-0	Hydrotreated ligh	t naphtha		n.a.	n.a.	n.a.	n.a.
		12.	Ecological Inforr	nation			
		No data availab	ole.				
		13. C	Disposal Conside	erations			
Waste Disposal Method: Disp		Dispose in accordance with local, state, and federal regulations.					
		14.	Transport Inform	nation			
LAND TRANS	PORT (US DOT):					
	•	-	d material [including pa	aint thinning	g, drying, ren	noving, or rec	lucing
DOT Haza	rd Class:	3	FLAMMABLE LIC	QUID			
UN/NA Nu	mber:	UN1263	Pa	cking Grou	:dr	111	
Additional Train	Additional Transport For DOT information, contact W.M. Barr Technical Services.						
		The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.			on, or others,		
			Regulatory Infor				
	ories' defined III Sections	[X] Yes [] No [X] Yes [] No [] Yes [X] No	Acute (immediate) He Chronic (delayed) He Fire Hazard Sudden Release of P Reactive Hazard	alth Hazaro	ł		

Page: 6 Printed: 09/15/2014 Revision: 09/05/2014 Supersedes Revision: 04/08/2013

CAS #Hazardous Components (Chemical Name)64742-49-0Hydrotreated light naphtha

Other US EPA or State Lists

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

Regulatory Information Statement:	All components of this material are listed on the TSCA Inventory or are exempt.		
	16. Other Information		
Revision Date:	09/05/2014		
Preparer Name:	W.M. Barr EHS Department (901)775-0100		
Additional Information About	No data available.		
This Product:			
Company Policy or Disclaimer:	The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.		