

Safety Data Sheet

Issue Date: 28-Aug-2013 Revision Date: 23-Jan-2018 Version 2

1. IDENTIFICATION

Product Identifier

Product Name Onetime Lightweight Spackling

Other means of identification

SDS # RD-0038OPP-R2

Product Code 540 Series

Recommended use of the chemical and restrictions on use

Recommended Use For patching & filling small holes in drywall w/ no need to prime before painting.

Details of the supplier of the safety data sheet

Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

Emergency Telephone Number

Company Phone Number 918-825-5744

Fax: 918-825-5761

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance White paste Physical state Paste Odor Mild Acrylic/slight ammoniacal

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Soda lime borosilicate glass	65997-17-3	<20
Propylene Glycol	57-55-6	<1
Amorphous silica (glass)	7631-86-9	<1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Immediately flush with large quantities of water for at least 15 minutes until irritation

subsides. Get medical attention.

Skin Contact Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist.

Remove & wash contaminated clothing.

Inhalation Remove to fresh air. If breathing is difficult, leave area to obtain fresh air. If breathing

remains difficult, get medical attention.

Ingestion Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean

patient forward to maintain an open airway & prevent aspiration. Get immediate medical

Revision Date: 23-Jan-2018

attention.

Most important symptoms and effects

Symptoms Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact

with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and

sneezing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Medical Conditions Aggravated by Exposure: Asthma & asthma-like conditions may worsen

from prolonged or repeated exposure to dust, should sanding be performed.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Hazardous Combustion Products Carbon oxides. Nitrogen oxides (NOx).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Other Information Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots &

eye protection).

Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum

level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.

Revision Date: 23-Jan-2018

For Emergency Responders

Restrict access to spill area.

Environmental precautions

Environmental precautions

Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing this material to enter streams, ponds, estuaries, oceans or other waters unless in accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA Regional Office

Other: U.S. regulations may require reporting of spills of this material reaching surface waters if sheen is formed. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Clean-Up

Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Keep out of reach of children & pets. Do not take internally. Do not breathe vapors or dust. If dry sanding use NIOSH-approved dust mask. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing. Do not eat or drink while handling this material. In event of spill – see Section 6.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Stable under normal conditions of handling, use & storage. Store containers in a cool, dry location, away from direct sunlight & high temperatures. Protect from freezing. Store away from incompatible materials (caustics & oxidizers). Close container after each use & keep tightly closed when not in use. To maximize shelf life, store @ temperatures below 26C (80F).

Incompatible Materials

Oxidizing agents, Caustics.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Soda lime borosilicate glass	TWA: 1 fiber/cm3 respirable	-	-
65997-17-3	fibers: length >5 µm, aspect ratio		
	>=3:1, as determined by the		
	membrane filter method at		
400-450X magnification [4-mm			
objective], using phase-contrast			
illumination			
	TWA: 5 mg/m ³ inhalable fraction		

Amorphous silica (glass)

7631-86-9

- (vacated) TWA: 6 mg/m³ <1%
Crystalline silica
TWA: 20 mppcf
: (80)/(% SiO2) mg/m³ TWA

Appropriate engineering controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS. Provide appropriate local exhaust ventilation if

Revision Date: 23-Jan-2018

material is to be sanded.

Individual protection measures, such as personal protective equipment

Eye/Face ProtectionUse approved safety goggles or safety glasses. If necessary, refer to appropriate

regulations and standards. Refer to 29 CFR 1910.133 for eye and face protection

regulations.

Skin and Body Protection Skin: Wear chemical resistant rubber gloves for repeated or prolonged use.

Body: Not required w/ normal use. Refer to 29 CFR 1910.138 for appropriate skin and body

protection.

Respiratory Protection Avoid breathing of dust. Avoid breathing of vapors, mists or spray. If concentrations exceed

exposure limits specified, use a NIOSH-approved supplied air respirator. If protection factor exceeded, use self contained breathing apparatus (SCBA). A respiratory protection program that exceeds OSHA 1910.134 & ANSI Z88.2 requirements should be followed when conditions warrant respirator use. If dry sanding preferred, use approved

NIOSH/OSHA respirator.

General Hygiene Considerations Wash hands w/ soap & water before breaks & @ end of workday. Remove & wash

contaminated clothing prior to re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste

Appearance White paste Odor Mild Acrylic/slight ammoniacal

Color White Odor Threshold Not determined

Property Note: The information below is not Remarks • Method

note: The information below is not Remarks • Methor intended for use in preparing

product specifications

oH 7.0-10.0

Melting Point/Freezing Point ~ 0 °C / ~32 °F Boiling Point/Boiling Range ~ 100 °C / ~212 °F

Flash Point > 93.33 °C / > 200 °F Ceta Closed Cup

Evaporation Rate Not determined Flammability (Solid, Gas) Not determined

Flammability Limits in Air

Upper Flammability Limits
Lower Flammability Limit
Vapor Pressure
Vapor Density
Unknown
Unknown
Not established
Heavier than air

Relative Density ~0.40-0.60 @ 25 °C (77 °F)

Water Solubility
Soluble in water
Solubility in other solvents
Partition Coefficient
Auto-ignition Temperature
Decomposition Temperature
Kinematic Viscosity
Soluble in water
Not determined
Not determined
Not determined
Not determined

RD-0038OPP-R2 - Onetime Lightweight Spackling

Revision Date: 23-Jan-2018

Not determined **Dynamic Viscosity Explosive Properties** Not determined **Oxidizing Properties** Not determined

Other Information

VOC Content (%) 0.5% **VOC Content** < 10 g/L

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

Incompatible Materials

Oxidizing agents, Caustics.

Hazardous Decomposition Products

Carbon oxides. Nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Eye contact may result in tearing, redness & pain.

Skin Contact Prolonged and frequent contact may cause redness and irritation. Repeated skin contact

may cause dermatitis.

Inhalation Overexposure to vapors during application & curing may mildly irritate respiratory tract &

result in coughing & sneezing.

Ingestion May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Propylene Glycol	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
57-55-6			
Amorphous silica (glass) 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat)1 h

Information on physical, chemical and toxicological effects

Please see section 4 of this SDS for symptoms. **Symptoms**

Revision Date: 23-Jan-2018

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Not known to be human skin or respiratory sensitizers.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
Amorphous silica (glass)		Group 3		
7631-86-9		·		

Legend

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Target organ effects Acute: Eyes & Skin. Chronic: Skin.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

>5,000.00 mg/kg ATEmix (oral) **ATEmix (dermal)** >5,000.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Propylene Glycol	19000: 96 h Pseudokirchneriella	51400: 96 h Pimephales promelas	1000: 48 h Daphnia magna mg/L
57-55-6	subcapitata mg/L EC50	mg/L LC50 static 41 - 47: 96 h	EC50 Static 10000: 24 h Daphnia
		Oncorhynchus mykiss mL/L LC50	magna mg/L EC50
		static 51600: 96 h Oncorhynchus	
		mykiss mg/L LC50 static 710: 96 h	
		Pimephales promelas mg/L LC50	
Amorphous silica (glass)	440: 72 h Pseudokirchneriella	5000: 96 h Brachydanio rerio mg/L	7600: 48 h Ceriodaphnia dubia mg/L
7631-86-9	subcapitata mg/L EC50	LC50 static	EC50

Persistence/Degradability

Not tested for persistence & biodegradability.

Bioaccumulation

Not tested for bio-accumulation potential.

Mobility

Not tested for mobility in soil

Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Revision Date: 23-Jan-2018

US EPA Waste Number

Not applicable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

<u>IMDG</u> Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E	ENCS	IECSC	KECL	PICCS	AICS
			LINCS					
Soda lime borosilicate glass	Χ	Х	Х	Present	Χ	Present	Х	Х
Propylene Glycol	Х	Х	Х	Present	Χ	Present	Х	Х
Amorphous silica (glass)	Х	Х	Х	Present	Χ	Present	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardNoFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

SARA 313

Not determined

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Revision Date: 23-Jan-2018

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Propylene Glycol 57-55-6	X		X
Amorphous silica (glass) 7631-86-9		X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	0	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	1	0	0	X

Issue Date:28-Aug-2013Revision Date:23-Jan-2018Revision Note:New formula

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet