


SAFETY DATA SHEET

1. Identification

HIL0109755	
Cinnamon Air Freshener	
02-15-2019	
HILLYARD INC 302 North 4th Street St. Joseph, MO 64501 United States	
816-383-8285	
1-800-424-9300	
02	
02-15-2019	
AIR FRESHENER	
None known.	
Flammable aerosols	Category 1
	Cinnamon Air Freshener 02-15-2019 HILLYARD INC 302 North 4th Street St. Joseph, MO 64501 United States 816-383-8285 1-800-424-9300 02 02-15-2019 AIR FRESHENER None known.

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
OSHA defined hazards	Not classified.	

Label elements



3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	60 - 80
Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Cinnamal		104-55-2	1 - 2.5
Other components below r	eportable levels		0.1 - 1

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment	Firefighters must use standard protective equipment including flame retardant coat, helmet with

Firefighters must use standard protective equipment including flame retardant coat, helmet with and precautions for firefighters face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

> In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Fire fighting

equipment/instructions

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of Personal precautions, low areas. Many gases are heavier than air and will spread along ground and collect in low or protective equipment and confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing emergency procedures during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре		Va	lue	
Acetone (CAS 67-64-1)	PEL		24	00 mg/m3	
			10	00 ppm	
Propane (CAS 74-98-6)	PEL		18	00 mg/m3	
			10	00 ppm	
US. ACGIH Threshold Li	mit Values				
Components	Туре		Va	lue	
Acetone (CAS 67-64-1)	STEL		50	0 ppm	
	TWA		25	0 ppm	
Butane (CAS 106-97-8)	STEL		10	00 ppm	
US. NIOSH: Pocket Guid	e to Chemical Hazards				
Components	Туре		Va	lue	
Acetone (CAS 67-64-1)	TWA		59	0 mg/m3	
			25	0 ppm	
Butane (CAS 106-97-8)	TWA		19	00 mg/m3	
			80	0 ppm	
Propane (CAS 74-98-6)	TWA		18	00 mg/m3	
			10	00 ppm	
ogical limit values					
ACGIH Biological Expos	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)		Asstans	L luine e	*	
ACELUTIE (CAS 07-04-1)	25 mg/l	Acetone	Urine	2	

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.
Individual protection measures	such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

· · · · · · · · ·	
Appearance	
Physical state	Gas.
Form	Aerosol. Liquefied gas.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	2.4 % estimated
Flammability limit - upper (%)	11.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	60 - 70 psig @20C estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	869 °F (465 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Heat of combustion (NFPA 30B)	32.03 kJ/g estimated

Product name: Cinnamon Air Freshener

Oxidizing properties	Not oxidizing.
Specific gravity	0.713 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity	Narcotic effects. May cause an allergic skin reaction.
•	· · ·

Test Desults	0	• ·
Species Test Results		Components
		Acetone (CAS 67-64-1)
		Acute
		Dermal
> 7426 mg/kg, 24 Hours	Guinea pig	LD50
> 9.4 ml/kg, 24 Hours		
> 7426 mg/kg, 24 Hours	Rabbit	
> 9.4 ml/kg, 24 Hours		
		Inhalation
55700 ppm, 3 Hours	Rat	LC50
132 mg/l, 3 Hours		
50.1 mg/l		
		Oral
5800 mg/kg	Rat	LD50
2.2 ml/kg		
		Butane (CAS 106-97-8)
		Acute
		Inhalation
1237 mg/l, 120 Minutes	Mouse	LC50
52 %, 120 Minutes		
1355 mg/l	Rat	
		Cinnamal (CAS 104-55-2)
		<u>Acute</u>
		Dermal
• •	Rabbit	LD50
1260 ml/kg, 24 Hours		
620 mg/kg		
50.1 mg/l 5800 mg/kg 2.2 ml/kg 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l > 1000 mg/kg, 24 Hours 1260 ml/kg, 24 Hours	Mouse	LD50 Butane (CAS 106-97-8) <u>Acute</u> Inhalation LC50 Cinnamal (CAS 104-55-2) <u>Acute</u>

Components	Species	Test Results	
	Rat	> 1200 mg/kg	
Inhalation			
Vapor			
LC50	Rat	477 ppm, 8 Hours	
		69 ppm, 4 Hours	
Oral			
LD50	Guinea pig	3400 mg/kg	
	Mouse	2225 mg/kg	
	Rat	2220 mg/kg	
ropane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
	e based on additional component data not sh		
Skin corrosion/irritation	Prolonged skin contact may cause tempora	ry irritation.	
Serious eye damage/eye rritation	Causes serious eye irritation.		
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause an allergic skin reaction.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcin	nogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation of Carcinogenicity		
Not listed. OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)		
Not regulated. US. National Toxicology Pro	ogram (NTP) Report on Carcinogens		
Not listed.			
Reproductive toxicity	This product is not expected to cause repro-	ductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the product.		
12. Ecological informatior			
Ecotoxicity		tally hazardous. However, this does not exclude the ave a harmful or damaging effect on the environment	
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Aquatic			

Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown. **Persistence and degradability** No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-oc	coefficient n-octanol / water (log Kow)		
Acetone	-0.24		
Butane 2.89			
Propane	2.36		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT


UN number UN proper shipping name Transport hazard class(es)	UN1950 Aerosols, flammable, (each not exceeding 1 L capacity)
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ

IAI	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo aircraft	Allowed with restrictions.
	Cargo aircraft only	Allowed with restrictions.
	Packaging Exceptions	LTD QTY
IM	DG	
	UN number	UN1950
	UN proper shipping name	AEROSOLS

Product name: Cinnamon Air Freshener



15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export	t Notification (40 CFR 707, Subpt. D)
Not regulated.	
CERCLA Hazardous Subst	ance List (40 CFR 302.4)
Acetone (CAS 67-64-1)	
SARA 304 Emergency rele	ase notification
Not regulated.	
OSHA Specifically Regulat	ed Substances (29 CFR 1910.1001-1050)
Not regulated.	

Superfund Amendments and R Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No	SARA)		
SARA 302 Extremely hazar	dous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
Cinnamal		104-55-2	1 - 2.5	-
Other federal regulations				
Clean Air Act (CAA) Section	n 112 Hazardous Air Polluta	nts (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	n 112(r) Accidental Release	Prevention (40 CFR	68.130)	
Butane (CAS 106-97-8) Propane (CAS 74-98-6)				
Safe Drinking Water Act (SDWA)	Not regulated.			
Drug Enforcement Adn Chemical Code Numbe	ninistration (DEA). List 2, Es r	ssential Chemicals (21 CFR 1310.02(b) and	l 1310.04(f)(2) and
Acetone (CAS 67-6 Drug Enforcement Adm	4-1) ninistration (DEA). List 1 & 2	6532 2 Exempt Chemical	Mixtures (21 CFR 1310	.12(c))
Acetone (CAS 67-6 DEA Exempt Chemical	4-1) Mixtures Code Number	35 %WV		
Acetone (CAS 67-6		6532		
US state regulations				
US. California Controlled S	ubstances. CA Department	of Justice (Californi	a Health and Safety Co	ode Section 11100)
Not listed. US. California. Candidate C (a))	chemicals List. Safer Consu	mer Products Regu	ations (Cal. Code Reg	s, tit. 22, 69502.3, subd.
Acetone (CAS 67-64-1) Butane (CAS 106-97-8) US. Massachusetts RTK - S	Substance List			
Acetone (CAS 67-64-1) Butane (CAS 106-97-8)				
Propane (CAS 74-98-6)				
US. New Jersey Worker and	d Community Right-to-Know	/ Act		
Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)				
	nd Community Right-to-Kno	ow Law		
Acetone (CAS 67-64-1) Butane (CAS 106-97-8)	, <u>,</u>			
Propane (CAS 74-98-6) US. Rhode Island RTK				
Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)				
	65 Water and Toxic Enforcemen listed as carcinogens or repro		ition 65): This material i	s not known to contain
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Che	emical Substances (A	ICS)	No
Product name: Cinnamon Air Fresh	ener			SDS US

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Revision date	02-15-2019 02-15-2019
Version #	02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Hazard(s) identification: Prevention Hazard(s) identification: Response GHS: Classification