

SAFETY DATA SHEET
LIQUITEX COLOURED GESSO (GREY)

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification**Product identifier****Product name** LIQUITEX COLOURED GESSO (GREY)**Product number** D012180**Recommended use of the chemical and restrictions on use****Application** Primer for Oil and Acrylic Painting**Details of the supplier of the safety data sheet****Supplier** ColArt Americas Inc.
11 Constitution Avenue
Piscataway
New Jersey 08855 - 1396
USA
1-732-562-0770
R.Enquiries@colart.co.uk**Contact Person** Regulatory Manager**Manufacturer****Emergency telephone number****Emergency telephone** For health information only call 1-800-628-3385 Piscataway NJ 08855.**2. Hazard(s) identification****Classification of the substance or mixture****Physical hazards** Not Classified**Health hazards** Not Classified**Environmental hazards** Not Classified**Label elements****Hazard statements** NC Not Classified**3. Composition/information on ingredients****Mixtures****Composition comments** -**4. First-aid measures****Description of first aid measures****Inhalation** Not relevant.**Ingestion** Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.**Eye contact** Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.**5. Fire-fighting measures**

LIQUITEX COLOURED GESSO (GREY)

Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

6. Accidental release measures

Methods and material for containment and cleaning up

Methods for cleaning up Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers.

7. Handling and storage

Precautions for safe handling

Usage precautions No specific recommendations.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container. Store at moderate temperatures in dry, well ventilated area.

8. Exposure Controls/personal protection

Exposure controls

Appropriate engineering controls No specific ventilation requirements.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection No specific hand protection noted.

Other skin and body protection No specific recommendations

Hygiene measures Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Paste
Color	Various colors.
Odor	Characteristic.
pH	pH (concentrated solution): 8.5-9.5
Initial boiling point and range	> 100°C @ 760 mm Hg
Vapour density	> 1
Relative density	1.4-1.6 @ 20°C
Solubility(ies)	Miscible with water

10. Stability and reactivity

Stability Stable at normal ambient temperatures.

LIQUITEX COLOURED GESSO (GREY)

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid freezing.

Hazardous decomposition products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Information on toxicological effects

General information No specific health hazards known.

Acute and chronic health hazards No specific health hazards known.

12. Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 01 12 waste paint and varnish other than those mentioned in 08 01 11

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DoT).

UN Number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

No transport warning sign required.

Packing group

Not applicable.

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

LIQUITEX COLOURED GESSO (GREY)**Regulatory Status**

This product has been evaluated by a toxicologist and labelled for acute and chronic health hazards in accordance with the Labelling of Hazardous Art Materials Regulation and Federal Regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act. This product conforms to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects.

This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the AP (Approved Product) Seal, meaning this product bears no chronic or acute human health hazards.

16. Other information

Revision date	7/30/2015
Revision	3
Supersedes date	7/30/2015
Hazard statements in full	H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.