

## MATERIAL SAFETY DATA SHEET

01520 - 1004

MSDS #: 557

Page 1 of 3

Chartpak, Inc.  
One River Road  
Leeds, MA 01053  
Phone: 413-584-5446 or 800-628-1910

VH 875

Emergency Medical Number: 888-786-0972

Creation Date: April 1, 2007

**Section One: Product Information**

Product Name: Grumbacher Japan Drier  
Product Sizes: 2.5 oz  
Product Class: Mediums

**Section Two: Ingredients**

Ingredients	CAS Number	% by Weight	PEL/TLV
Petroleum Distillates	N/A	66%	N/A

**Section Three: Hazards Identification**

WARNING: COMBUSTIBLE. VAPOR HARMFUL. MAY BE HARMFUL IF SWALLOWED. CANCER AGENT BASED ON EXPERIMENTAL DATA.

CONTAINS: NAPHTHALENE, PETROLEUM DISTILLATES.

KEEP OUT OF REACH OF CHILDREN.

**Section Four: First Aid Measures**

Inhalation: Move to fresh air.  
Skin Contact: Wash with soap and water.  
Eye Contact: Flush with copious amounts of water.  
Ingestion: If swallowed, get prompt medical attention.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 5572

**MATERIAL SAFETY DATA SHEET****MSDS #: 557**

Page 2 of 3

**Section Five: Fire Fighting Measures**

Flash Point: 129F

Flammability Limits (% by volume): Lower: Not explosive Upper: Not explosive

Extinguishing Media: Foam, carbon dioxide, or dry chemical

Special Fire Fighting Measures: No special fire fighting procedures required

Unusual Fire and Explosion Hazards: Combustible

**Section Six: Accidental Release Measures**

Wipe up with absorbent material.

**Section Seven: Handling and Storage**

Handling: Use only with adequate ventilation.

Storage: Do not store or use near heat or flame.

**Section Eight: Exposure Controls and Personal Protection**

Respiratory Protection and Special Ventilation Requirements: Use exhaust fan to assure adequate cross-ventilation.

Other Protective Equipment (Gloves, Goggles, Etc.): None

Work/Hygiene Practices: PRECAUTIONS: Avoid ingestion. Wash hands immediately after use. When using, do not eat, drink, or smoke. Do not store or use near heat or flame. Use only with adequate ventilation.

**Section Nine: Physical and Chemical Properties**

Boiling Point: Not determined Melting Point: Not determined

Vapor Pressure: Not determined Specific Gravity: Not determined

Specific Vapor Density (AIR = 1): Not determined Evaporation Rate (Butyl Acetate = 1): Not determined

Solubility in Water: Negligible Reactivity in Water: Non-reactive

Appearance and Odor: Dark yellow liquid; petroleum odor

**Section Ten: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: None known

Chemical Incompatibility: None known

Hazardous Decomposition: None known

Hazardous Polymerization: Will not occur

## MATERIAL SAFETY DATA SHEET

MSDS #: 557

Page 3 of 3

**Section Eleven: Toxicological Information**

IARC Monographs: No  
 National Toxicology Program: No  
 OSHA Regulated: No  
 Effects/Symptoms of Acute Exposure: Irritation of eyes or chest  
 Effects/Symptoms of Chronic Exposure: None expected  
 Medical Conditions Usually Aggravated By Overexposure of This Product: None known

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations

**Section Fourteen: Transport Information**

ORM-D Consumer Commodity  
 Flammable Liquid, n.o.s. (petroleum distillates), 3, UN1993, III (120F TCC) Ltd Qtys, EmS# F-E, S-E  
 Consumer Commodity, 9, ID8000, packing instruction 910

**Section Fifteen: Regulatory Information**

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

**Section Sixteen: Other Information****HMIS Code**

Health 2  
 Flammability 2  
 Reactivity 0  
 Personal Protection C

Chartpak, Inc. is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D-4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.