MSDS for #01565 - MAIMERI OIL N		Page 1
INDUSTRIA M	IAIMERI S.P.A.	Revision nr.1 Dated 3/9/2014
AUXILIARY PRODUCTS	58626 Dryng me	dium Printed on 3/9/2014 Page n. 1 / 8
	Safety data she	et
ECTION 1. Identification of the s	ubstance/mixture and of the	company/undertaking
1. Product identifier		
Code: Product name	58626 AUXILIARY PRODUCTS 586	26 Dryng medium
2. Relevant identified uses of the substance	or mixture and uses advised against	
Intended use	Improves the drying rate of oil col	ours.
.3. Details of the supplier of the safety data sl	neet	
Name Full address District and Country	INDUSTRIA MAIMERI S.P.A. Via Gianni Maimeri, 1 20060 Mediglia Italia Tel. +39 02 906981	(MI)
e-mail address of the competent person responsible for the Safety Data Sheet	Fax +39 02 90698999 schedesicurezza@maimeri.it	
Product distribution by	_	MAIMERI 1 20060 BETTOLINO DI MEDIGLIA
.4. Emergency telephone number		
For urgent inquiries refer to	Australia : 131126 USA: 1 800 222 1222 Regno Unito NHS Direct (UK): +44	(0) 845 46 47
SECTION 2. Hazards identification	۱.	
.1. Classification of the substance or mixture.		
	ct thus requires a safety datasheet the	C Regulation 1272/2008 (CLP) (and subsequent at complies with the provisions of EC Regulation ren in sections 11 and 12 of this sheet.
.1.1. Regulation 1272/2008 (CLP) and followin	g amendments and adjustments.	
Hazard classification and indication: Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H336 Aquatic Chronic 2 H411		
2.1.2. 67/548/EEC and 1999/45/EC Directives ar	nd following amendments and adjustm	ents.
Danger Symbols: Xn-N		
R phrases: 10-51/53-65-	66-67	
The full wording of the Risk (R) and hazard (H)	phrases is given in section 16 of the she	et.
Item Numbers: 01565-1049		BEPY 8.1.21 - SDS 1003 Page
		6

	ISTRIA M	AIMERI S.P.A	•	Revision nr.1 Dated 3/9/2014	
AUXILIARY PR	RODUCTS	58626 Dryng	medium	Printed on 3/9/2014 Page n. 2 / 8	
SECTION 2. Hazards ide	entification / >>				
2.2. Label elements.					
Hazard labelling pursuant	to EC Regulation 127	2/2008 (CLP) and subsequent a	mendments and supp	lements.	
Hazard pictograms:		¥2			
Signal words:	Danger				
Hazard statements:					
H226 H304	Flammable liquid and May be fatal if swallow	vapour. ved and enters airways.			
	May cause drowsines				
H411		ith long lasting effects.			
Precautionary statements	:				
P101		eded, have product container or	label at hand.		
P102 P210	Keep out of reach of c		aces No smoking		
P210 P280		<pre>/ sparks / open flames / hot surfa s / protective clothing / eye prote</pre>			
P301+P310		nediately call a POISON CENTE			
P501		container to in accordance with I			
Contains: .3. Other hazards.	White Spirit				
Information not available.	sition/informati	ion on ingredients.			
SECTION 3. Compo a.1. Substances.	sition/informati	ion on ingredients.			
SECTION 3. Compo 3.1. Substances. Information not relevant.	sition/informati	ion on ingredients.			
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification.		on on ingredients.	Classificati	on 1272/2008 (CLP).	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification.	Conc. %. Classific		Flam. Liq. 3 H2	26, Asp. Tox. 1 H304, STOT SE 3 H336,	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS EC. 919-446-0	Conc. %. Classific	cation 67/548/EEC.	Flam. Liq. 3 H2		
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS EC. 919-446-0 INDEX	Conc. %. Classific 50 - 54 R10, R66, F	cation 67/548/EEC.	Flam. Liq. 3 H2	26, Asp. Tox. 1 H304, STOT SE 3 H336,	
SECTION 3. Compo s.1. Substances. Information not relevant. s.2. Mixtures. Contains: Identification. White Spirit CAS S EC. 919-446-0 INDEX Reg. no. 01-2119-4	Conc. %. Classific 50 - 54 R10, R66, F 458049-33	cation 67/548/EEC.	Flam. Liq. 3 H2	26, Asp. Tox. 1 H304, STOT SE 3 H336,	
SECTION 3. Compo s.1. Substances. Information not relevant. s.2. Mixtures. Contains: Identification. White Spirit CAS EC. 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 DNOBUTYL ETHER	cation 67/548/EEC.	Flam. Liq. 3 H2: Aquatic Chronic	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS EC. 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC	Conc. %. Classific 50 - 54 R10, R66, F 458049-33	cation 67/548/EEC.	Flam. Liq. 3 H2	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS EC. 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC CAS. 112-34-5 EC. 203-961-6 INDEX. 603-096-00-8 Note: Upper limit is not inc	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 DNOBUTYL ETHER 0 - 0,05 Xi R36 Cluded into the range.	Cation 67/548/EEC. R67, Xn R65, N R51/53, Note P	Flam. Liq. 3 H2: Aquatic Chronic Eye Irrit. 2 H319	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo s.1. Substances. Information not relevant. s.2. Mixtures. Contains: Identification. White Spirit CAS EC. 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC CAS. 112-34-5 EC. 203-961-6 INDEX. 603-096-00-8 Note: Upper limit is not inc	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 DNOBUTYL ETHER 0 - 0,05 Xi R36 Cluded into the range.	cation 67/548/EEC.	Flam. Liq. 3 H2: Aquatic Chronic Eye Irrit. 2 H319	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS 4 EC. 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC CAS. 112-34-5 (EC. 203-961-6 INDEX. 603-096-00-8 Note: Upper limit is not interest of the Rise	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 DNOBUTYL ETHER 0 - 0,05 Xi R36 Cluded into the range. Sk (R) and hazard (H) p xn = Harmful(Xn), C = Corros	Cation 67/548/EEC. R67, Xn R65, N R51/53, Note P	Flam. Liq. 3 H2; Aquatic Chronic Eye Irrit. 2 H319	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC CAS. 112-34-5 (EC. 203-961-6 INDEX. 603-096-00-8 Note: Upper limit is not into The full wording of the Ris T+ = Very Toxic(T+), T = Toxic(T), N = Dangerous for the Environment	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 SNOBUTYL ETHER 0 - 0,05 Xi R36 Cluded into the range. Sk (R) and hazard (H) p xn = Harmful(Xn), C = Corros Sh(N)	Cation 67/548/EEC. R67, Xn R65, N R51/53, Note P	Flam. Liq. 3 H2; Aquatic Chronic Eye Irrit. 2 H319	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS EC. 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC CAS. 112-34-5 EC. 203-961-6 INDEX. 603-096-00-8 Note: Upper limit is not ind The full wording of the Ris T+ = Very Toxic(T+), T = Toxic(T), N = Dangerous for the Environment SECTION 4. First aid	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 R10, R66, F 0 - 0,05 Xi R36 Cluded into the range. Sk (R) and hazard (H) p Xn = Harmful(Xn), C = Corros nt(N) Cludes d measures. Resures.	Cation 67/548/EEC. R67, Xn R65, N R51/53, Note P	Flam. Liq. 3 H2; Aquatic Chronic Eye Irrit. 2 H319 the sheet. E = Explosive(E), F+ = Extrer	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo 3.1. Substances. Information not relevant. 3.2. Mixtures. Contains: Identification. White Spirit CAS 4 EC. 919-446-0 INDEX Reg. no. 01-21194 ETHYLENE GLYCOL MC CAS. 112-34-5 EC. 203-961-6 INDEX. 603-096-00-8 Note: Upper limit is not ind The full wording of the Ris T+ = Very Toxic(T+), T = Toxic(T), N = Dangerous for the Environment SECTION 4. First aid Not specifically necessary 4.2. Most important sympton	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 DNOBUTYL ETHER D - 0,05 Xi R36 Cluded into the range. sk (R) and hazard (H) p Xn = Harmful(Xn), C = Corros nt(N) d measures. Measures. Measures. Mobservance of good poms and effects, both	cation 67/548/EEC. R67, Xn R65, N R51/53, Note P ohrases is given in section 16 of sive(C), Xi = Irritant(Xi), O = Oxidizing(O), E industrial hygiene is recommence a acute and delayed.	Flam. Liq. 3 H2; Aquatic Chronic Eye Irrit. 2 H319 the sheet. E = Explosive(E), F+ = Extrer	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	
SECTION 3. Compo .1. Substances. Information not relevant. .2. Mixtures. Contains: Identification. White Spirit CAS Reg. no. 01-21194 ETHYLENE GLYCOL MC CAS. 112-34-5 (EC. 203-961-6 INDEX. 603-096-00-8 Note: Upper limit is not ind The full wording of the Ris T+ = Very Toxic(T+), T = Toxic(T), N = Dangerous for the Environment SECTION 4. First aid Not specifically necessary .2. Most important symptometal	Conc. %. Classific 50 - 54 R10, R66, F 458049-33 DNOBUTYL ETHER D - 0,05 Xi R36 Cluded into the range. sk (R) and hazard (H) p Xn = Harmful(Xn), C = Corros nt(N) d measures. Measures. Measures. Mobservance of good poms and effects, both	cation 67/548/EEC. R67, Xn R65, N R51/53, Note P phrases is given in section 16 of sive(C), Xi = Irritant(Xi), O = Oxidizing(O), E	Flam. Liq. 3 H2; Aquatic Chronic Eye Irrit. 2 H319 the sheet. E = Explosive(E), F+ = Extrer	26, Asp. Tox. 1 H304, STOT SE 3 H336, 2 H411, EUH066, Note P	

Page 2 of 8

Revision nr.1 Dated 3/9/2014 Printed on 3/9/2014 Page n. 3 / 8

AUXILIARY PRODUCTS SECTION 4. First aid measures./>>

4.3. Indication of any immediate medical attention and special treatment needed.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

58626 Dryng medium

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

AUXILIARY PRODUCTS

58626 Dryng medium

Revision nr.1 Dated 3/9/2014 Printed on 3/9/2014 Page n. 4 / 8

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Information not available.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration. Personal protection equipment must comply with the rules in force indicated below. HAND PROTECTION

Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure. EYE PROTECTION

Use of protective airtight goggles (ref. standard EN 166) recommended.

SKIN PROTECTION Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

· · · · · · · · · · · · · · · · · · ·	ор			
Appearance		liquid		
Colour		SLIGHTL	= =	
Odour		WHITE SP	PIRIT	
Odour threshold.		Not availa	ble.	
pH.				
Melting point / freezing point.		Not availa	ble.	
Initial boiling point.		Not availa	ble.	
Boiling range.		Not availa	ble.	
Flash point.	>	23 °	C.	
Evaporation Rate		Not availa	ble.	
Flammability of solids and gases		Not availa	ble.	
Lower inflammability limit.		Not availa	ble.	
Upper inflammability limit.		Not availa	ble.	
Lower explosive limit.		Not availa	ble.	
Upper explosive limit.		Not availa	ble.	
Vapour pressure.		Not availa	ble.	
Vapour density		Not availa	ble.	
Relative density.			(g/l	
Solubility		- /	IN WHITE SP	IRIT
Partition coefficient: n-octanol/water		Not availa	ble.	
Auto-ignition temperature.		Not availa	ble.	
Decomposition temperature.		Not availa		
Viscosity		Not availa		
Explosive properties		Not availa		
Oxidising properties		Not availa		
9.2. Other information.				
VOC (Directive 1999/13/EC) :		54 16 %	- 454,92	g/litre.
VOC (volatile carbon) :		54.04 %		g/litre.
		0-,0- /0		ginue.

MSDS for #01565 - MAIMERI OIL MEDIUM

INDUSTRIA MAIMERI S.P.A.

AUXILIARY PRODUCTS

58626 Dryng medium

Revision nr.1 Dated 3/9/2014 Printed on 3/9/2014 Page n. 5 / 8

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

White Spirit	
LD50 (Oral).	> 5000 mg/Kg
LD50 (Dermal).	> 4 mg/Kg

SECTION 12. Ecological information.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity.

White Spirit	
LC50 (96h) - for Fish.	< 30
EC50 (48h) - for Algae / Aquatic Plants.	< 22
EC50 (72h) - for Crustacea.	< 10

12.2. Persistence and degradability. Information not available.

12.3. Bioaccumulative potential. Information not available.

12.4. Mobility in soil. Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

mg/l mg/l mg/l

12.6. Other adverse effects.

AUXILIARY PRODUCTS

58626 Dryng medium

Revision nr.1 Dated 3/9/2014 Printed on 3/9/2014 Page n. 6 / 8

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

Road and rail transport:

ADR/RID Class: Packing Group: Label: Nr. Kemler: Limited Quantity. Tunnel restriction code. Proper Shipping Name: Special Provision:	3 UN: III 3 30 5 L (D/E) PAINT or PAINT 640E	1263 T RELATED MATERIAL	
Carriage by sea (shipping):			
IMO Class: Packing Group: Label: EMS: Marine Pollutant. Proper Shipping Name:	3 UN: III 3 F-E , <u>S-E</u> YES PAINT or PAINT	1263 E F RELATED MATERIAL (Wh	ite Spirit)
Transport by air:			
IATA: Packing Group: Label: Cargo:	3 UN: III 3	1263	
Packaging instructions:	366	Maximum quantity:	220 L 3
Pass.: Packaging instructions: Special Instructions: Proper Shipping Name:	355 A3, A72 PAINT or PAINT	Maximum quantity:	60 L
SECTION 15. Regulatory	information.		
15.1. Safety, health and environm		slation specific for the sub	stance or mixture.
Seveso category.	9ii, 6		

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

i iouuci.	
Point.	3 - 40

Substances in Candidate List (Art. 59 REACH).

None.

Item Numbers: 01565-1049

Revision nr.1 Dated 3/9/2014 Printed on 3/9/2014 Page n. 7 / 8

SECTION 15. Regulatory information. ... / >>

AUXILIARY PRODUCTS

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention: None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

58626 Dryng medium

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10 R36	FLAMMABLE. IRRITATING TO EYES.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level

Revision nr.1 Dated 3/9/2014 Printed on 3/9/2014 Page n. 8 / 8

AUXILIARY PRODUCTS SECTION 16. Other information. .../>>

- PNEC: Predicted no effect concentration

- REACH: EC Regulation 1907/2006

- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments

- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. The Merck Index. 10th Edition
- 9. Handling Chemical Safety
- 10. Niosh Registry of Toxic Effects of Chemical Substances
- 11. INRS Fiche Toxicologique (toxicological sheet)
- 12. Patty Industrial Hygiene and Toxicology
- 13. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 14. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

58626 Dryng medium

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified: 01 / 02 / 03 / 06 / 07 / 08 / 09 / 11 / 12 / 13 / 14 / 15 / 16.

Page 8 of 8

Page 8 of 8