## SAFETY DATA SHEET

11/6/2015

#### **SECTION I - IDENTIFICATION**

Material Name WEBER ARCHIVAL COPAL PAINTING MEDIUM

Company Information Martin/F. Weber Company 2727 Southampton Road Philadelphia, PA 19154-1293 Phone: 215-677-5600 Fax: 1-215-677-3336 Email: compliance@weberart.com

In the event of a transportation emergency, call CHEM-TEL (Contract MIS0003081). Within the US, Canada, Puerto Rico and the US Virgin Islands, call 1-800-255-3924. Outside North America, call collect 1-813-248-0585.

For health emergencies call the Poison Control Center: 1-800-222-1222

#### SECTION II - HAZARDS IDENTIFICATION

#### Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Skin Irritation - Category 2 Eye Irritation - Category 2 Skin Sensitization - Category 1 Aspiration Hazard - Category 1 Hazardous to the Aquatic Environment - Chronic - Category 2 Flammable Liquid 3

#### **GHS Label Elements**

Symbol(s)



Signal Word(s) Danger

#### Hazard Statement(s)

Causes serious eye irritation Causes skin irritation Flammable liquid and vapour May be fatal if swallowed and enters airways. May cause an allergic skin reaction Toxic to aquatic life with long lasting effects

#### Precautionary Statement(s)

#### Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Keep cool. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up.

#### Response

Get medical advice/attention. Specific treatment (see label). Do NOT induce vomiting. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Rinse skin with water [or shower]. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Collect spillage. IF SWALLOWED:

Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

#### SECTION III - COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

		PEL/TLV	Max		
Hazardous Ingredients	CAS/EC #	(MG/M#)	% Weight	NTP	IARC
PETROLEUM DISTILLATES		525.00	20.80019	Ν	Ν
TURPENTINE	8006-64-2	560.00	57.53000	Ν	Ν

#### SECTION IV - FIRST AID MEASURES

FIRST AID MEASURES: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. Get prompt medical attention. If skin contact occurs, wash with soap and water for 5 minutes.

#### SECTION V - FIRE FIGHTING MEASURES

 FLASH POINT (METHOD): 91°F (33°C)
 AUTO

 EXPLOSION LIMITS IN AIR (% BY VOLUME): LEL 0.8% - UEL 6%
 EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical (Class B) or Halon

 FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
 Wear self-contained breathing apparatus.

 UNUSUAL FIRE & EXPLOSION HAZARDS: FLAMMABLE. FLAMMABLE

### SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with noncombustible, absorbent material. For waste disposal, see Section XIII

### SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

### SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use only with adequate ventilation. OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): When using wear impermeable protective gloves. WORK/HYGIENE PRACTICES: Wash hands immediately after use. When using do not eat, drink or smoke. Keep away from eyes. ENGINEERING CONTROLS: Do not store or use near heat or flame.

FOR HOME USE: CHILD-PROOF PACKAGING REQUIRED IN CONFORMANCE WITH 16CFR1700.15 a), b), and c) and meet the child test protocol requirements of one of CSA-Z76.1, ISO 8317 or 16 CFR 1700.20 or a standard that is at least equivalent.

AUTOIGNITION TEMPERATURE: N/A

### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 300° - 315° F (149° - 157°C) VAPOR PRESSURE: 5mm Hg SPECIFIC VAPOR DENSITY (AIR=1): N/A SOLUBILITY IN WATER: N/A MELTING POINT: N/A

SPECIFIC GRAVITY: 0.88 REACTIVITY IN WATER: NON-REACTIVE

### SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A STABILITY: STABLE CONDITIONS TO AVOID: N/A INCOMPATIBILITY (MATERIALS TO AVOID): N/A HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and smoke

### SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: SKIN IRRITANT. EYE IRRITANT. EXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTACT MAY RESULT IN REDNESS OR PAIN OF THE EYES. The summated LD50 is >50000 mg/kg. The summated LD50 is >50000 mg/kg.

The summated LC50 is 11119 mg/cubic meter.

This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

#### SECTION XII - ECOLOGICAL INFORMATION

Aquatic Hazard Statement(s)

Toxic to aquatic life with long lasting effects

#### SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE. WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

#### SECTION XIV - TRANSPORTATION INFORMATION

U.S. D.O.T. Domestic Ground: ORM-D Consumer Commodity Ocean Freight: UN 1263 Paint Related Material, Class 3 PG III, Limited Quantity Air Freight: DO NOT SHIP via air without special packaging and labeling. Contact your air carrier for detailed instructions.

#### SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 EPA SARA TITLE III CHEMICAL LISTINGS NONE

SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355): NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372): NONE

Page 3

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS: BUTYLATED HYDROXY TOLUENE STODDARD SOLVENT TURPENTINE

SUPPLEMENTAL STATE COMPLIANCE INFORMATION:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED UNDER NEW JERSEY'S RIGHT TO KNOW PROGRAM: BUTYLATED HYDROXY TOLUENE TURPENTINE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRING NOTIFICATION TO THE STATE OF WASHINGTON UNDER THEIR CHILDREN'S SAFE PRODUCTS ACT: NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN FLORIDA'S TOXIC SUBSTANCE LIST: Butylated hydroxytoluene (bht) Turpentine

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MAINE'S PRIORITY CHEMICAL LIST: NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS CONSIDERED BY VERMONT AS BEING OF VERY HIGH CONCERN TO CHILDREN: NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MASSACHUSETTS HAZARDOUS SUBSTANCE LIST: Butylated hydroxytoluene (BHT) Turpentine

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MICHIGAN'S CRITICAL MATERIALS REGISTER: NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MINNESOTA'S HAZARDOUS SUBSTANCES LIST: 2,6-Di-tert-butyl-p-cresol Turpentine

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN PENNSYLVANIA'S HAZARDOUS SUBSTANCES LIST: Phenol, 2,6-bis(1,1dimethylethyl)-4-meth

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling:

# DANGER:FLAMMABLE. Harmful or fatal if swallowed. VAPOR HARMFUL. SKIN IRRITANT. EYE IRRITANT. Contains: PETROLEUM DISTILLATES, TURPENTINE

PRECAUTIONS: Wash hands immediately after use. When using wear impermeable protective gloves, or do not eat, drink or smoke. Keep away from eyes. Do not store or use near heat or flame. Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.** 

FIRST AID TREATMENT: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. Get prompt medical attention. If skin contact occurs, wash with soap and water for 5 minutes.

This adult product is certified to comply with the Consumer Product Safety Act (CPSA), the Poison Prevention Packaging Act, the Federal Hazardous Substances Act, (FHSA) and its Labeling for Hazardous Art Materials Act (LHAMA).

### SECTION XVI - OTHER INFORMATION

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

LAST REVISION DATE: 11/06/2015

Prepared by Duke OEM Toxicology

### **BRAND NAMES**

THIS SDS APPLIES TO THE FOLLOWING BRAND NAMES

Brand Name	SKU	SKU Description
WEBER ARCHIVAL COPAL PAINTING MEDIUM	1781	4 OZ, 118 ML
	1783	16 OZ, 473 ML