

1. Identification

Product identifier Williamsburg Alkyd Resin

Other means of identification

Product code 6009022

Recommended use Artist paint

Recommended restrictions None known.

Manufacturer / Importer / Supplier / Distributor information

Company name Golden Artist Colors, Inc.

Address 188 Bell Rd., New Berlin
NY 13411
US

Telephone 607-847-6154

E-mail gavett@goldenpaints.com

Contact person Ben Gavett

Emergency phone number 607-847-6154

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Skin corrosion/irritation Category 2

Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated exposure Category 2 (Kidney)

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer. May cause damage to organs (Kidney) through prolonged or repeated exposure.

Precautionary statement

Prevention Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist/vapors/spray. Wash hands thoroughly after handling.

Response If exposed or concerned: Call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Static accumulating flammable liquids

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2

Hazardous to the aquatic environment, long-term hazard Category 2

Supplemental information

Hazard statement Toxic to aquatic life with long lasting effects.

Response Collect spillage.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Stoddard solvent	8052-41-3	20-30
Ethylbenzene	100-41-4	<0.2

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move injured person into fresh air and keep person calm under observation. Get medical attention if any discomfort continues.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort continues.

Most important symptoms/effects, acute and delayed Overexposure to mists/vapors of this product may cause headache, dizziness, nausea, and respiratory tract irritation. Symptoms include itching, burning, redness and tearing. Defats the skin.

Indication of immediate medical attention and special treatment needed Treat symptomatically.

General information Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

5. Fire-fighting measures

Suitable extinguishing media Foam. Carbon dioxide (CO2). Dry chemical. Powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical During fire, gases hazardous to health may be formed. Solvent vapors may form explosive mixtures with air.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Avoid inhalation of vapors/dust and contact with skin and eyes. Wear suitable protective clothing. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Remove sources of ignition. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container.

Environmental precautions Do not discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Read label before use. Use only in well-ventilated areas. Avoid inhalation of vapors/spray and contact with skin and eyes. Wear appropriate personal protective equipment. The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not smoke and do not spray near a naked flame or other sources of ignition. Do not smoke and do not spray near an open flame or other sources of ignition.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Keep in a cool, well-ventilated place. Store away from incompatible materials. Keep out of reach of children.

MSDS for #01747- WILMSBURG ALKYD OIL MED
Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3
Stoddard solvent (CAS 8052-41-3)	PEL	100 ppm
		2900 mg/m3
		500 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm

US NIOSH Pocket Guide to Chemical Hazards: Ceiling Limit Value and Time Period (if specified)

Components	Type	Value
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	435 mg/m3
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm
		350 mg/m3

US NIOSH Pocket Guide to Chemical Hazards: Short Term Exposure Limit (STEL)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.7 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Use explosion-proof equipment. Provide adequate ventilation and minimize the risk of inhalation of vapors and mists. Provide easy access to water supply or an emergency shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Risk of contact: Wear approved safety glasses or goggles.

Skin protection

Hand protection

Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Other

Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.

Respiratory protection

Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

MSDS for #01747 - WMSBNG ARTS OIL MED

Appearance	Brown. Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Brown.
Odor	Mineral spirits
Odor threshold	Not available.
pH	7.3 - 8.7
Melting point/freezing point	Not available.
Initial boiling point and boiling range	428 °F (220 °C)
Flash point	102.2 °F (39.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1 %
Flammability limit - upper (%)	6 %
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.95
Solubility(ies)	Insoluble in water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 200 cP
Viscosity temperature	77 °F (25 °C)
Other information	
Density	0.95 g/cm ³
Percent volatile	30

10. Stability and reactivity

Reactivity	Stable at normal conditions.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Will not occur.
Conditions to avoid	Heat, sparks, flames. Contact with incompatible materials.
Incompatible materials	Oxidizing agents. Reducing agents. Alkalis. Strong acids. Sulfuric acid.
Hazardous decomposition products	Carbon oxides. Hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Ingestion may cause nausea, headache and dizziness.
Inhalation	May cause central nervous system effects. Vapors and mist may irritate throat and respiratory system and cause coughing.
Skin contact	Causes skin irritation.
Eye contact	May cause eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Overexposure to mists/vapors of this product may cause headache, dizziness, nausea, and respiratory tract irritation. Defats the skin.

Information on toxicological effects

Williamsburg Alkyd Resin

SDS US

906524 - Version #: 01 - Revision date: - Issue date: 13-December-2013

Item Numbers: 01747-3004, 01747-3006, 01747-3007

Page 4 of 8

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	18156 mg/kg
<i>Inhalation</i>		
LC50	Rat	55000 mg/m ³
<i>Oral</i>		
LD50	Rat	3500 mg/kg
Stoddard solvent (CAS 8052-41-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	May cause eye irritation.	
Respiratory sensitization	None known.	
Skin sensitization	None known.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspect cancer hazard.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Reproductive toxicity	Not available.	
Specific target organ toxicity - single exposure	Vapors may cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (Kidney) through prolonged or repeated exposure.	
Aspiration hazard	Not classified.	
Chronic effects	May cause damage to the kidneys. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.	

12. Ecological information

Ecotoxicity	Toxic to aquatic life with long lasting effects.		
Components			
Species			
Test Results			
Ethylbenzene (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Daphnia	2.1 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	32 - 88 mg/l, 96 hours
		Fathead minnow (Pimephales promelas)	12.1 mg/l, 96 hours
Persistence and degradability	The product is not expected to be readily biodegradable.		
Bioaccumulative potential	Has the potential to bioaccumulate.		
Partition coefficient n-octanol / water (log Kow)			
Ethylbenzene (CAS 100-41-4)	3.15		
Stoddard solvent (CAS 8052-41-3)	3.16 - 7.15		
Mobility in soil	No data available.		
Mobility in general	The product contains organic solvents which will evaporate easily from all surfaces.		
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.		

Disposal instructions	Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not discharge into drains, water courses or onto the ground. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations. When your own wastewater treatment plant is not available, collect entire waste and then charge to a licensed industrial waste management professional with manifests for industrial waste.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Waste from residues / unused products	Dispose in accordance with all applicable regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound
Transport hazard class(es)	3
Subsidiary class(es)	-
Packing group	III
Special precautions for user	Not available.
Special provisions	B1, B52, IB3, T2, TP1, TP29
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint related material
Transport hazard class(es)	3
Subsidiary class(es)	-
Packaging group	III
Environmental hazards	Yes
Labels required	Not available.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1263
UN proper shipping name	PAINT RELATED MATERIAL
Transport hazard class(es)	3
Subsidiary class(es)	-
Packaging group	III
Environmental hazards	
Marine pollutant	Yes
Labels required	Not available.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

General information ADR: This material is not regulated if in a container of 119 gallon (450 L) capacity or less.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylbenzene (CAS 100-41-4) LISTED

MSDS for #01747 - WMSBRG ARTIST OIL MED

Hazard Categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance No
 SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylbenzene	100-41-4	<0.2

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

WARNING: This product contains chemicals known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Ethylbenzene (CAS 100-41-4)
 Stoddard solvent (CAS 8052-41-3)

US. New Jersey Worker and Community Right-to-Know Act

Ethylbenzene (CAS 100-41-4) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

Ethylbenzene (CAS 100-41-4)
 Stoddard solvent (CAS 8052-41-3)

US. Rhode Island RTK

Ethylbenzene (CAS 100-41-4)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Ethylbenzene (CAS 100-41-4)

International Inventories


Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 13-December-2013
 Revision date -
 Version # 01



References

HSDB (2005)
IARC Monographs. Overall Evaluation of Carcinogenicity
ACGIH
US. IARC Monographs on Occupational Exposures to Chemical Agents
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.

This SDS contains revisions in the following section(s):

1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16.