

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 1/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product name : MEDIUM A PEINDRE TURNER

Product code : N135501. 193. 195..

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Registered company name : Max Sauer SAS.

Address : 2 rue Lamarck.22000.Saint Briec.France.

Telephone : 0033(0)296682000. Fax : 0033(0)296770065.

mail@raphael.fr

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.**SECTION 2 : HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture****In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Highly flammable (F, R 11).

Acute oral toxicity: harmful (Xn, R 22).

Acute cutaneous toxicity: harmful (Xn, R 21).

Acute inhalation toxicity: harmful (Xn, R 20).

This mixture represents an aspiration risk due to its low viscosity: harmful (Xn, R 65).

Skin irritation (Xi, R 38).

Eye irritation (Xi, R 36).

Skin sensitisation (Xi, R 43).

Aquatic environmental hazard, chronic toxicity: toxic (N, R 51/53).

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07



GHS05



GHS09



GHS08



GHS02

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 2/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

Signal Word :

DANGER

Product identifiers :

EC 926-141-6	ESSENCE DE TÉRÉBENTHINE
CAS 919-857-5	HYDROCARBONS AROMATIQUES, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2%
603-004-00-6	HYDROCARBURES, C9-C11 N-ALKANES, ISOALKANES, CYCLIQUES <2% AROMATIQUES
CAS 919-446-0	N-BUTANOL
	HYDROCARBURES, C9-C12, N-ALKANES, ISOALKANES, CYCLIQUES, AROMATIQUES
	(2-25%)
649-423-00-8	KEROSINE (PETROLEUM), HYDRODESULFURIZED
603-001-00-X	METHANOL

Hazard statements :

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements - General :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

Precautionary statements - Prevention :

P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see ... on this label).
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 3/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

P362 Take off contaminated clothing and wash before reuse.
 P363 Wash contaminated clothing before reuse.
 P370 + P378 In case of fire: Use ... for extinction.
 P391 Collect spillage.
 Precautionary statements - Storage :
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 Precautionary statements - Disposal :
 P501 Dispose of contents/container to ...

2.3. Other hazards

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European Chemical Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	67/548/EEC	Note	%
ESSENCE DE TÉRÉBENTHINE	GHS07, GHS09, GHS08 Dgr Acute Tox. 4, H302 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Aquatic Chronic 2, H411	Xn,N Xn;R20/21/22-R65 Xi;R36/38-R43 N;R51/53 R10		25 <= x % < 50
CAS: 64742-47-8 EC: 926-141-6 HYDROCARBONS AROMATICS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2%	GHS08 Dgr Asp. Tox. 1, H304 EUH:066	Xn Xn;R65 R66		10 <= x % < 25
CAS: 919-857-5 HYDROCARBURES, C9-C11 N-ALKANES, ISOALKANES, CYCLIQUES <2% AROMATIQUES	GHS07, GHS08 Dgr Asp. Tox. 1, H304 STOT SE 3, H336 EUH:066	Xn Xn;R65 R10 R66-R67		2.5 <= x % < 10
INDEX: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6 N-BUTANOL	GHS02, GHS05, GHS07 Dgr Flam. Liq. 3, H226 Acute Tox. 4, H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336	Xn Xn;R22 Xi;R37/38-R41 R10 R67	[1]	2.5 <= x % < 10
CAS: 919-446-0 HYDROCARBURES, C9-C12, N-ALKANES, ISOALKANES, CYCLIQUES, AROMATIQUES (2-25%)	GHS09, GHS07, GHS08 Dgr Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066	Xn,N Xn;R65 N;R51/53 R10 R66-R67		1 <= x % < 2.5

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 4/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

INDEX: 649-423-00-8 CAS: 64742-81-0 EC: 265-184-9 KEROSINE (PETROLEUM), HYDRODESULFURIZED	GHS08 Dgr Asp. Tox. 1, H304	Xn Xn;R65	[1]	1 <= x % < 2.5
INDEX: 603-001-00-X CAS: 67-56-1 EC: 200-659-6 METHANOL	GHS02, GHS06, GHS08 Dgr Flam. Liq. 2, H225 Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 STOT SE 1, H370	T,F T;R23/24/25-R39/23/24/25 F;R11	[1]	0 <= x % < 1

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of splashes or contact with eyes :**

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 5/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 6/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Never inhale this mixture.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid eye contact with this mixture at all times.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 7/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
67-56-1	260	200	-	-	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
71-36-3	20 ppm	-	-	-	-
64742-81-0	200 mg/m3	-	-	-	-
67-56-1	200 ppm	250 ppm	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
71-36-3	100 ml/m3	310 mg/m3	1(I)	DFG, Y
67-56-1	200 ml/m3	270 mg/m3	4(II)	DFG, EU, H, Y

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
71-36-3	-	-	50	150	-	84
67-56-1	200	260	1000	1300	(12)	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
71-36-3	-	50 ppm	-	-	-
67-56-1	200 ppm	250 ppm	-	-	-

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 8/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state :

Viscous liquid.

Important health, safety and environmental information

pH :

Not stated.

Neutral.

Boiling point/boiling range :

> 35°C

Flash Point :

15.00 °C.

Vapour pressure (50°C) :

Below 110 kPa (1.10 bar).

Density :

> 1

Water solubility :

Insoluble.

Viscosity:

v < 7 mm²/s (40°C)

Melting point/melting range :

Not specified.

Self-ignition temperature :

Not specified.

Decomposition point/decomposition range :

Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 9/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

May cause an allergic reaction by skin contact.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Aspiration hazard :

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 10/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

14.1. UN number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

II

14.5. Environmental hazards

- Environmentally hazardous material :

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	5 L	163 650 640C	E2	2	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	II	5 L	F-E,S-E	163	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	II	353	5 L	364	60 L	A3 A72	E2

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 11/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

	3	-	II	Y341	1 L	-	-	A3 A72	E2
--	---	---	----	------	-----	---	---	-----------	----

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Regulation EC 1272/2008 modified by regulation EC 618/2012
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

- Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).


Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=3 Inflammability=3 Instability/Reactivity=1 Specific Risk=none

**- Swiss ordinance on the incentive tax on volatile organic compounds :**

67-63-0 propane-2-ol (alcool isopropylique)

71-36-3 butane-1-ol (alcool butylique)

64-17-5 éthanol, seulement s'il s'agit d'alcools impropres à la consommation (art. 31 de la loi fédérale sur l'alcool)

67-56-1 méthanol (alcool méthylique)

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 12/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :



Harmful



Dangerous for the environment



Highly flammable

Contains :

603-001-00-X

603-004-00-6

EC 926-141-6

649-423-00-8

CAS 919-446-0

CAS 919-857-5

Risk phrase :

R 51/53

R 43

R 36/38

R 20/21/22

R 11

R 65

Safety phrase :

S 2

S 23

S 23

S 23

S 23

S 29

S 36/37

S 46

S 13

S 25

S 26

S 51

S 56

S 64

S 9

S 24

METHANOL

N-BUTANOL

HYDROCARBONS AROMATICS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2%

KEROSINE (PETROLEUM), HYDRODESULFURIZED

ESSENCE DE TÉRÉBENTHINE

HYDROCARBURES, C9-C12, N-ALKANES, ISOALKANES, CYCLIQUES, AROMATIQUES

(2-25%)

HYDROCARBURES, C9-C11 N-ALKANES, ISOALKANES, CYCLIQUES <2% AROMATIQUES

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

May cause sensitisation by skin contact.

Irritating to eyes and skin.

Harmful by inhalation, in contact with skin and if swallowed.

Highly flammable.

Harmful: may cause lung damage if swallowed.

Keep out of the reach of children.

Ne pas respirer les gaz

Ne pas respirer les fumées.

Ne pas respirer les vapeurs.

Ne pas respirer les aérosols.

Do not empty into drains.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

Keep away from food, drink and animal feedingstuffs.

Utiliser et conserver à l'écart de toute flamme ou source d'ignition ou d'étincelles, source de chaleur ou appareil électrique en fonctionnement- Ne pas fumer

Avoid contact with eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Use only in well-ventilated areas.

Dispose of this material and its container to hazardous or special waste collection point.

If swallowed, rinse mouth with water (only if the person is conscious).

Keep container in a well-ventilated place.

Avoid contact with skin.

Title for H, EUH and R indications mentioned in section 3 :

H225

Highly flammable liquid and vapour.

H226

Flammable liquid and vapour.

H301

Toxic if swallowed.

H302

Harmful if swallowed.

H304

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Max Sauer SAS

Version 1.1 (02/06/2014) - Page 13/13

Name : MEDIUM A PEINDRE TURNER - N135501. 193. 195.

H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs .
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
R 10	Flammable.
R 11	Highly flammable.
R 20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R 22	Harmful if swallowed.
R 23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R 36/38	Irritating to eyes and skin.
R 37/38	Irritating to respiratory system and skin.
R 39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R 41	Risk of serious damage to eyes.
R 43	May cause sensitisation by skin contact.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65	Harmful: may cause lung damage if swallowed.
R 66	Repeated exposure may cause skin dryness or cracking.
R 67	Vapours may cause drowsiness and dizziness.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS02 : Flame

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS08 : Health hazard

GHS09 : Environment