

Oil Painting Medium Quick Drying

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 31-01-2014

Revision date:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Oil Painting Medium Quick Drying
 Product code : 1108
 Type of product : Solvents
 Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
 Industrial/Professional use spec : Industrial
 For professional use only
 Use of the substance/mixture : Medium
 Function or use category : Solvents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Old Holland Classic Colours Since 1664
 Nijendal 36
 3972 KC Driebergen Rijsenburg - Nederland
 T 0031 343 518 224 - F 0031 343 516 342
info@oldholland.com - www.oldholland.com

1.4. Emergency telephone number

| Country | Organisation/Company | Address | Emergency number |
|-------------|--|--|------------------|
| NETHERLANDS | Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals | Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht | +31 30 274 88 88 |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226
 Acute Tox. 4 (Oral) H302
 Acute Tox. 4 (Inhalation:dust,mist) H332
 Skin Irrit. 2 H315
 Eye Irrit. 2 H319
 Skin Sens. 1 H317
 STOT SE 3 H336
 Asp. Tox. 1 H304
 Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

Xn; R65
 N; R51/53
 R10
 R66
 R67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Portugese Gum Turpentine

Hazard statements (CLP) :

H226 - Flammable liquid and vapour
 H302+H332 - Harmful if swallowed or if inhaled
 H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P261 - Avoid breathing vapours, mist, spray
 P273 - Avoid release to the environment
 P301+P310 - IF SWALLOWED: Immediately call a doctor
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P331 - Do NOT induce vomiting

EUH phrases :

EUH066 - Repeated exposure may cause skin dryness or cracking

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification according to Directive 67/548/EEC |
|--|---|---------|---|
| Portugese Gum Turpentine | (CAS No) 8006-64-2 (EC no) 232-350-7 (EC index no) 650-002-00-6 | 50 - 75 | Xn; R65 N; R51/53 R10 R66 R67 |
| Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%) | (EC no) 919-446-0 (REACH-no) 01-2119458049-33 | 0 - 50 | Xn; R65 N; R51/53 R10 R66 R67 |
| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
| Portugese Gum Turpentine | (CAS No) 8006-64-2 (EC no) 232-350-7 (EC index no) 650-002-00-6 | 50 - 75 | Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
| Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%) | (EC no) 919-446-0 (REACH-no) 01-2119458049-33 | 0 - 50 | STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |

Full text of R- and H-phrases: see section 16

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Repeated exposure may cause skin dryness or cracking. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause an allergic skin reaction. May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing vapors, mist, spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, mist, spray.

MSDS for #01750 - OLD HOLLAND OIL MED Oil Painting Medium Quick Drying

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Explosion-free electrical equipment and lighting with earth.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Solvent.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment : Gloves. Dust/aerosol mask. Safety glasses. Avoid all unnecessary exposure. Protective clothing.



Hand protection : Wear protective gloves. Since the product consists of several substances, it is possible to estimate the durability of the glove material beforehand and it therefore needs to be tested before use. Gloves must be replaced after each use and whenever signs of wear or perforation appear.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Colourless.

Odour : characteristic.

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Self ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapour

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

Relative density : No data available

Solubility : No data available

Log Pow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidising properties : No data available

Explosive limits : No data available

20-02-2014

EN (English)

4/8

MSDS for #01750 - OLD HOLLAND OIL MED
Oil Painting Medium Quick Drying

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established. Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful if inhaled.

| Oil Painting Medium Quick Drying | |
|---|---------------------------|
| ATE (oral) | 500,000 mg/kg bodyweight |
| ATE (dust,mist) | 1,500 mg/l/4h |
| Portugese Gum Turpentine (8006-64-2) | |
| LD50 oral rat | 5,76 mg/m ³ |
| ATE (oral) | 500,000 mg/kg bodyweight |
| ATE (dermal) | 1100,000 mg/kg bodyweight |
| ATE (dust,mist) | 1,500 mg/l/4h |
| Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%) | |
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rat | > 4 mg/kg |

| | |
|---|--|
| Skin corrosion/irritation | : Causes skin irritation. Repeated exposure may cause skin dryness or cracking |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified Based on available data, the classification criteria are not met |
| Carcinogenicity | : Not classified Based on available data, the classification criteria are not met |
| Reproductive toxicity | : Not classified Based on available data, the classification criteria are not met |
| Specific target organ toxicity (single exposure) | : May cause drowsiness or dizziness. |
| Specific target organ toxicity (repeated exposure) | : Not classified Based on available data, the classification criteria are not met |
| Aspiration hazard | : May be fatal if swallowed and enters airways. |
| Potential Adverse human health effects and symptoms | : Harmful if swallowed. Harmful if inhaled. |
| Other information | : Risk of aspiration pneumonia. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

| Portugese Gum Turpentine (8006-64-2) | |
|---|-----------|
| EC50 Daphnia 1 | 14,1 mg/l |

MSDS for #01750 - OLD HOLLAND OIL MED
Oil Painting Medium Quick Drying

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)

| | |
|--------------------------------|----------|
| EC50 Daphnia 1 | 7,8 g/l |
| EC50 other aquatic organisms 1 | 3,59 g/l |

12.2. Persistence and degradability

Oil Painting Medium Quick Drying

Persistence and degradability : May cause long-term adverse effects in the environment.

Portugese Gum Turpentine (8006-64-2)

Persistence and degradability : May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Oil Painting Medium Quick Drying

Bioaccumulative potential : Not established.

Portugese Gum Turpentine (8006-64-2)

Bioaccumulative potential : Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

: Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to to an authorized waste treatment plant.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

| | |
|---------------|--------|
| UN-No (ADR) | : 1263 |
| UN-No.(IATA) | : 1263 |
| UN-No. (IMDG) | : 1263 |
| UN-No.(ADN) | : 1263 |

14.2. UN proper shipping name

Proper Shipping Name : PAINT / PAINT RELATED MATERIAL

Transport document description : UN 1263 PAINT / PAINT RELATED MATERIAL, 3, III, (D/E)

14.3. Transport hazard class(es)

| | |
|--------------------------|------|
| Class (UN) | : 3 |
| Classification code (UN) | : F1 |
| Class (IATA) | : 3 |
| Class (IMDG) | : 3 |
| Class (ADN) | : 3 |
| Hazard labels (UN) | : 3 |



14.4. Packing group

Packing group (UN) : III

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : No

MSDS for #01750 - OLD HOLLAND OIL MED
Oil Painting Medium Quick Drying

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 30
 Classification code (UN) : F1
 Orange plates :



Special provision (ADR) : 163, 650, 640E
 Transport category (ADR) : 3
 Tunnel restriction code : D/E
 Limited quantities (ADR) : 5L
 Excepted quantities (ADR) : E1
 EAC code : +3YE

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.6.4. Inland waterway transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions
 Contains no REACH candidate substance

Seveso Information :

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Abbreviations and acronyms : ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road). ATE: Acute Toxicity Estimated. CAS: Chemical Abstracts Service (division of the American Chemical Society). CLP: Classification, Labeling and Packaging. CMR: Carcinogenic, Mutagenic, Reprotoxic. CSA: Chemical Safety Assessment. CSR: Chemical Safety Report. DNEL: Derived No Effect Level (for human). EC50: Median Effective Concentration (required to induce a 50% effect). EINECS: European Inventory of Existing Commercial Chemical Substances. GHS: Globally Harmonized System of Classification and Labelling of Chemicals. IATA: International Air Transport Association. IMDG: International Maritime Code for Dangerous Goods. LC50: Lethal concentration, 50 percent. LD50: Lethal dose, 50 percent. PBT: Persistent, Bio accumulating and Toxic. PNEC: Predicted No Effect Concentration (for environment). REACH: Registration, Evaluation and Authorisation of Chemical substances. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail). SVHC: Substances of Very High Concern. vPvB: very Persistent, very Bio accumulating.

MSDS for #01750 - OLD HOLLAND OIL MED
Oil Painting Medium Quick Drying

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Other information

: **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. REACH Disclaimer:
 This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).

Full text of R-, H- and EUH-phrases::

| | |
|-------------------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment — Chronic Hazard, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| Skin Sens. 1 | Sensitisation — Skin, category 1 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H226 | Flammable liquid and vapour |
| H302 | Harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H411 | Toxic to aquatic life with long lasting effects |
| R10 | Flammable |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment |
| R65 | Harmful: may cause lung damage if swallowed |
| R66 | Repeated exposure may cause skin dryness or cracking |
| R67 | Vapours may cause drowsiness and dizziness |
| N | Dangerous for the environment |
| Xn | Harmful |

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product