MSDS for #01558 - MAIMERI CLAS	SSICO OIL	Page
INDUSTRIA M	IAIMERI S.P.A.	Revision nr.27 Dated 10/7/2014
CLASSICO OIL COLOURS	03026 Super rapid White	Printed on 10/7/2014 Page n. 1 / 8
	Safety data sheet	
SECTION 1. Identification of the s	ubstance/mixture and of the compar	y/undertaking
1.1. Product identifier		
Code: Product name	03026 CLASSICO OIL COLOURS 03026 Super i	rapid White
1.2. Relevant identified uses of the substance	or mixture and uses advised against	
Intended use	Oil colour.	
1.3. Details of the supplier of the safety data s	heet	
Name Full address District and Country	INDUSTRIA MAIMERI S.P.A. Via Gianni Maimeri, 1 20060 Mediglia Italia Tel. +39 02 906981	(MI)
e-mail address of the competent person responsible for the Safety Data Sheet	Fax +39 02 90698999 schedesicurezza@maimeri.it	
Product distribution by	INDUSTRIA MAIMERI S.P.A. VIA G.MAIMERI 1 (MI) ITALY	20060 BETTOLINO DI MEDIGLIA
I.4. Emergency telephone number		
For urgent inquiries refer to	Australia : 131126 USA:  1 800 222 1222 Regno Unito NHS Direct (UK): +44 (0) 845 46 4	47
amendments and supplements). The produ 1907/2006 and subsequent amendments.		with the provisions of EC Regulation
2.1.1. Regulation 1272/2008 (CLP) and followir	-	
Hazard classification and indication: Aquatic Acute 1 H400 Aquatic Chronic 1 H410		
2.1.2. 67/548/EEC and 1999/45/EC Directives a	nd following amendments and adjustments.	
Danger Symbols: N		
R phrases: 50/53		
The full wording of the Risk (R) and hazard (H	) phrases is given in section 16 of the sheet.	
2.2. Label elements.		
Hazard labelling pursuant to EC Regulation 12	272/2008 (CLP) and subsequent amendments and sup	plements.
Hazard pictograms:		
$\checkmark$		

Item Numbers: 01558-1043, 01558-1044

Page 1 of 8

EPY 8.1.21

INDU	JSTRI	A MAIMERI S.	<b>P.A</b> .	Revision nr.27 Dated 10/7/2014
CLASSICO OIL			per rapid White	Printed on 10/7/2014 Page n. 2 / 8
CTION 2. Hazards id	lentification.	/>>		
Signal words:	Warning			
Hazard statements:	Vany taxia ta	aquatic life with long lasting effe	ata	
H410 Precautionary statement		aquatic life with long lasting energy	cis.	
P273 P391	Avoid releas Collect spilla	e to the environment.		
P501		contents / container to in accordar	nce with local and national no	orms
. Other hazards.				
Information not available	9.			
ECTION 3. Comp	osition/inf	ormation on ingredien	ts.	
1. Substances.				
Information not relevant.				
2. Mixtures.				
Contains: Identification.	Conc. %.	Classification 67/548/EEC.	Classifica	tion 1272/2008 (CLP).
Zinc oxide			Chabolinda	(off (1),2,2000 (off)).
CAS. 1314-13-2	50 - 54	N R50/53	Aquatic Acute	1 H400 M=1, Aquatic Chronic 1 H410
EC. 215-222-5 INDEX. 030-013-00-7				
Reg. no. 01-2119	463881-32-000			
CAS. 112-34-5	0 - 0,05	ETHER Xi R36	Eye Irrit. 2 H3	19
EC. 203-961-6				
INDEX. 603-096-00-8 Distillates (petroleum),		light		
CAS. 64742-47-8		Xn R65, Note 4	Asp. Tox. 1 H	304, Note 4
EC. 265-149-8 INDEX. 649-422-00-2				
1,2,4-TRIMETHYLBENZ				
CAS. 95-63-6 EC. 202-436-9	0 - 0,05	R10, Xn R20, Xi R36/37/38, N R51/53		226, Acute Tox. 4 H332, Eye Irrit. 2 H319, 15, STOT SE 3 H335, Aquatic Chronic 2 H411
INDEX. 601-043-00-3				
Note: Upper limit is not i				
-	. ,	zard (H) phrases is given in secti		
T+ = Very Toxic(T+), T = Toxic(T N = Dangerous for the Environm		.), C = Corrosive(C), Xi = Irritant(Xi), O = Oxi	idizing(O), E = Explosive(E), F+ = Extr	emely Flammable(F+), F = Highly Flammable(F),
ECTION 4. First a	id measu	res.		
1. Description of first air		e of good industrial hygiene is rec	commended	
		ects, both acute and delayed.		
		bable to the product have been r	•	
3. Indication of any imm Information not available		al attention and special treatme	ent needed.	
ECTION 5. Firefig	hting mea	isures.		
1. Extinguishing media.				
SUITABLE EXTINGUISI			der For product loss or leak	age that has not caught fire, water spray
		pours and protect those trying to		age that has not caught life, water splay
can be used to disperse		sours and protect those if ying to		
UNSUITABLE EXTINGL		IPMENT		
UNSUITABLE EXTINGL		IPMENT	es but can be used to cool	containers exposed to flames to prevent

CLASSICO OIL COLOURS 03026 Super rapid White

# SECTION 5. Firefighting measures. ... / >>

## 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters. GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6.** Accidental release measures.

- 6.1. Personal precautions, protective equipment and emergency procedures.
- Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

#### 7.2. Conditions for safe storage, including any incompatibilities.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s).

Information not available.

## **SECTION 8. Exposure controls/personal protection.**

#### 8.1. Control parameters.

Regulatory References:	
United Kingdom	EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits
	for use with the Control of Substances Hazardous to Health Regulations (as amended).
Éire	Code of Practice Chemical Agent Regulations 2011.
OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive
	2000/39/EC.
TLV-ACGIH	ACGIH 2012

Zinc oxide					
Threshold Limit Value.					
Туре	Country	TWA/8h		STEL/15	imin
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		5		15	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration.

Item Numbers: 01558-1043, 01558-1044

Revision nr.27 Dated 10/7/2014 Printed on 10/7/2014

Page n. 3/8

CLASSICO OIL COLOURS 03026 Super rapid White

# SECTION 8. Exposure controls/personal protection. .../>>

HAND PROTECTION

Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure. SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

#### RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

EYE PROTECTION

Use of protective airtight goggles (ref. standard EN 166) recommended.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9.** Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

9.1. Information on basic physical and chemical properties.					
Appearance		paste			
Colour		white			
Odour		OIL			
Odour threshold.		Not available.			
pH.					
Melting point / freezing point.		Not available.			
Initial boiling point.		Not available.			
Boiling range.		Not available.			
Flash point.	>	60 °C.			
Evaporation Rate		Not available.			
Flammability of solids and gases		Not available.			
Lower inflammability limit.		Not available.			
Upper inflammability limit.		Not available.			
Lower explosive limit.		Not available.			
Upper explosive limit.		Not available.			
Vapour pressure.		Not available.			
Vapour density		Not available.			
Relative density.		0,2 Kg/l			
Solubility		INSOLUBLE, DILUTE WITH WHITE SPIRIT			
Partition coefficient: n-octanol/water		Not available.			
Auto-ignition temperature.		Not available.			
Decomposition temperature.		Not available.			
Viscosity		Not available.			
Explosive properties		Not available.			
Oxidising properties		Not available.			
9.2. Other information.					
Solid content.		78,62 %			
VOC (Directive 1999/13/EC) :		0,15 % - 3,26 g/litre.			
VOC (volatile carbon) :		0,12 % - 2,77 g/litre.			
· · · · · ·					

# SECTION 10. Stability and reactivity.

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

Page 4 of 8

Revision nr.27 Dated 10/7/2014 Printed on 10/7/2014

Page n. 4/8

Page 4 of 8

CLASSICO OIL COLOURS 03026 Super rapid White

# SECTION 10. Stability and reactivity. ... / >>

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

#### **10.5. Incompatible materials.** Information not available.

### 10.6. Hazardous decomposition products.

Information not available.

### **SECTION 11.** Toxicological information.

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This product may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

#### 11.1. Information on toxicological effects.

Information not available.

### **SECTION 12. Ecological information.**

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

#### 12.1. Toxicity.

Information not available.

#### **12.2. Persistence and degradability.** Information not available.

**12.3. Bioaccumulative potential.** Information not available.

#### 12.4. Mobility in soil.

Information not available.

#### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.

# **SECTION 13.** Disposal considerations.

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

- Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
- Avoid littering. Do not contaminate soil, sewers and waterways.
- Waste transportation may be subject to ADR restrictions

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information.**

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

INDUS		MERI S.P.A.		Revision nr.27	
CLASSICO OIL CO		03026 Super ra		Dated 10/7/2014 Printed on 10/7/2014 Page n. 6 / 8	
ECTION 14. Transport infor	mation / >>				
Road and rail transport:					
ADR/RID Class: Packing Group:	9 UN: III	3082	•	^	
Label:	9		aff)		
Nr. Kemler:	90				
Limited Quantity.	5 L				
Tunnel restriction code.				NOS (Zine evide)	
Proper Shipping Name:	ENVIRONM	ENTALLY HAZARDOUS SUI	STANCE, LIQUID,	N.O.S. (Zinc oxide)	
Carriage by sea (shipping):					
IMO Class:	9 UN:	3082			
Packing Group: Label:	 9		an an		
EMS:	9 F-A, S-F			»< <u>₹</u> _>	
Marine Pollutant.	YES		9	$\sim$	
Proper Shipping Name:	ENVIRONM	ENTALLY HAZARDOUS SU	BSTANCE, LIQUID,	N.O.S. (Zinc oxide)	
Transport by air:					
ΙΑΤΑ:	9 UN:	3082			
Packing Group:	III	0002		$\sim$	
Label:	9		afilit,	N/Y/	
Cargo:			9		
Packaging instructions: Pass.:	964	Maximum quantity:	450 L 🚿	$\sim$	
Packaging instructions:	964	Maximum quantity:	450 L		
Special Instructions: Proper Shipping Name:	A97, A158 ENVIRONM	ENTALLY HAZARDOUS SU		NOS (Zinc oxide)	
INFORMATION ON TRANSPO					
ECTION 15. Regulator		a siclation ana ifia for the a	ubotonoo or mivtu		
5.1. Safety, health and environr Seveso category.	9i	egisiation specific for the s	ubstance or mixtu	re.	
Restrictions relating to the produc		ces pursuant to Appen XV/II to	EC Regulation 1907/	2006	
Product.			Lo regulation 19077	2000.	
Point. 3					
Substances in Candidate List (Art None.	. 59 REACH).				
Substances subject to authorisario None.	on (Annex XIV REACH	<u>i).</u>			
Substances subject to exportation None.	reporting pursuant to	(EC) Reg. 689/2008:			
Substances subject to the Rotterd	am Convention:				
Substances subject to the Stockho None.	olm Convention:				
Healthcare controls. Information not available.					
	at				
.2. Chemical safety assessme					
No chemical safety assessment	has been processed	t for the mixture and the subs	tances it contains.		
					PY 8.1.21 - SDS 1003

MSDS for #01558 - MAIMERI CLASSICO OIL

# INDUSTRIA MAIMERI S.P.A.

CLASSICO OIL COLOURS 03026 Super rapid White

Revision nr.27 Dated 10/7/2014 Printed on 10/7/2014 Page n. 7 / 8

# **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10	FLAMMABLE.
R20	HARMFUL BY INHALATION.
R36	IRRITATING TO EYES.
R36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
R50/53	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE
	AQUATIC ENVIRONMENT.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC
	ENVIRONMENT.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

EPY 8.1.21

# **CLASSICO OIL COLOURS** SECTION 16. Other information. ... / >>

# 03026 Super rapid White

Revision nr.27 Dated 10/7/2014 Printed on 10/7/2014 Page n. 8/8

# GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. The Merck Index. 10th Edition
- 9. Handling Chemical Safety
- 10. Niosh Registry of Toxic Effects of Chemical Substances
- 11. INRS Fiche Toxicologique (toxicological sheet)
- 12. Patty Industrial Hygiene and Toxicology
- 13. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 14. ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified: 02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.