

01597-1193

HAR1490- A June 1, 2015

MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING MERCURY COMPOUND

Page 1 of 6

1. Identification of the Preparation and of The Company

MICHAEL HARDING ARTIST OIL COLORS - COLORS CONTAINING MERCURY

Product Name and/or code: COMPOUND Effective Date: 1-Jun-15

Manufacturer: Michael Harding Art Materials Ltd.

36 Springdale Industrial Estate Cwmbran, Gwent NP44 -5BD, Wales

Information Contact: North America: 978-549-4029

UK/Europe: 44 (0) 1633 - 484-700

Emergency Contact: Contact your local Poison Control Center Product Use: ART MATERIAL - Consumer Product

2. Hazards Identification

Information pertaining to particular dangers

for man and environment.

This product has been classified as dangerous according to OSHA Hazard

Communication Standard (29 CFR 1910.1200)

Emergency Overview

WARNING! MAY CAUSE DAMAGE TO KIDNEY THROUGH PROLONGED OR REPEATED EXPOSURE.

Label Elements

Conforms to ASTM D-4236

Pictograms



GHS 07

Signal Word

WARNING!

Hazard Statement MAY CAUSE DAMAGE TO KIDNEY THROUGH PROLONGED OR REPEATED

EXPOSURE. May cause central nervous system effects. May cause mercury poisoning. Contact may cause eye and skin irritation.

Precaution Statement Do not apply heat. Do not eat. Wash hands and face before eating or

smoking. Ensure fresh air entry during application and drying. Avoid dust

or prolonged or repeated skin contact.

Children's Statement KEEP OUT OF REACH OF CHILDREN.

Classification of the Product:

NFPA Health 2 - May be harmful if inhaled or absorbed

Flammability 1 - Combustible if heated

Reactivity 0 - Stable

HMIS Health 2 - Moderate Hazard

Flammability 1 -Slight Hazard Physical Hazard 0 - Minimal Hazard

Filysical Hazaru 0 - Willilliai Hazaru

Regulation (EC) No. 1272/2008 Mercury compounds are classified in the Annex I of the regulation.

Export and Import of Dangerous Chemicals

Regulation (EC)No. 649/2012

This product and its ingredients are listed in the Annex I of the regulation.

Directive 67/548/EEC & Directive 1999/45/EC Mercury sulfide (CAS: 1344-48-5) H317, P261, P272, P280, P302+P352, P333+P313, P363, P501

Item Numbers: 01597-1193, 01597-1192 Page 1 of 6



MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING MERCURY COMPOUND

HAR1490- A June 1, 2015 Page 2 of 6

3.Composition/Information on Ingredients:

Substances:

The various products listed under Section 16 contain non-hazardous natural drying oils, organic and inorganic pigments, additives.

Hazardous Ingredients

Mercury sulfide (CAS: 1344-48-5) ----- 50.00% - 90.00%

Risk and Safety Phrases:

Ingredients are marked according to CLP Regulation (CLP-Regulation (EC) No 1272/2008) and according to DSD (Dangerous Substances Directive (67/548/EEC)) and DPD (Dangerous Preparations Directive (1999/45/EC)). These ingredients are regarded as trade secrets.

	4. First Aid Measures		
Inhalation	Supply fresh air. If required, provide artificial respiration. Consult with a		
Skin Contact	Remove any contaminated clothing. Wash affected area immediately		
	with water and soap and rinse thoroughly. If irritation persists, see a		
	physician.		
Eye Contact	Flush area with water, lifting the upper and lower lids until no evidence of		
	product remains. Get medical attention. Do not wear contact lenses while		
	handling.		
Ingestion	If swallowed, call physician immediately		
	5. Firefighting Measures		
Extinguishing Media	Water, foam, carbon dioxide or dry chemical equipment.		
Fire/Explosion Hazards	This product is not known to present any fire hazard.		
Flashpoint/Flammability	This product is not known to be combustible, but as a precaution keep		
	product in cool place.		
6	. Accidental Release Measures		
Environmental precautions	No product should be released to the environment without due care.		
Methods and Materials for Containment and	Contain spill. Recover as much as possible with sand, soil or similar		
Cleaning up	product. Place into closed container and store in a safe location to await		
	disposal. Wash the spill area with soap and water.		
	7. Handling and Storage		
Safe Handling	Use under ventilated conditions. Avoid eye contact. For personal		
	protection, we recommend that employees wash thoroughly after		
	handling product. Always wash before eating, smoking or using toilet		
	facilities. Keep container closed when not in use.		
Storage	Keep the sample in a cool dry ventilated area. Keep away from fire and		
	heating sources.		
8. Ехр	osure Controls/Personal Protection		
Personal Protective Equipment	Wear safety goggles and protective gloves to avoid dust contact.		

Exposure Limits

Page 2 of 6 Item Numbers: 01597-1193, 01597-1192



MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING MERCURY COMPOUND

HAR1490- A June 1, 2015 Page 3 of 6

Components with workplace control parameters

Componente with	Components with workplace control parameters						
Component	CAS-No.	Value	Control	Basis			
			parameters				
Mercury(II) sulfide	1344-48-5	TWA	0.025000	USA. ACGIH Threshold Limit Values			
			mg/m3	(TLV)			
	Remarks	Central Nervous System impairment					
		Kidney damage					
		Substances for which there is a Biological Exposure Index or Indices (see BEI® section)					
		Not classifia	Not classifiable as a human carcinogen				
		Danger of cutaneous absorption					
		varies					
		TWA	0.050000	USA. NIOSH Recommended			
			mg/m3	Exposure Limits			
		Potential for dermal absorption					
		С	0.100000	USA. NIOSH Recommended			
			mg/m3	Exposure Limits			

Respiratory and Ventilation

Skin Protection

Wear approved NIOSH/MSHA respirator if exposure to mist or vapor exceed applicable PEL/TLV limits. Use in accordance with manufacturer's use limitations and OSHA STANDARD 1910-34. Local ventilation may be used to prevent routine inhalation.

Handle with non-porous nitrile gloves. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full Contact Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash protection Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-

mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for

any specific use scenario.

Eye Protection

Safety glasses conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Item Numbers: 01597-1193, 01597-1192 Page 3 of 6



MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING MERCURY COMPOUND

HAR1490- A June 1, 2015 Page 4 of 6

9. Physical and Chemical Properties				
Appearance	Viscous colored oil paints			
Physical State	Solid - Paste			
Color	See product list in Section 16			
Odor	Slightly aromatic.			
Boiling Point	Greater than 100°C/ 212°FGreater than 100°C/ 212°FGreater than 100°C/			
	212°FGreater than 100°C/ 212°FGreater than 100°C/ 212°FGreater than			
	100°C/ 212°F			
Freezing Point	Not applicable			
State (pH)	8.5 - 9.2			
Specific Gravity	1.0 - 2.0			
Viscosity	Not determined (Viscous material)			
Flashpoint	Greater than 230°C/ 446°F			
Vapor Pressure	Not applicable			
Vapor Density	Not applicable			
Solubility in water	Not miscible			
	10. Stability and Reactivity			
Reactivity:	Reaction with reducing agents.			
Chemical Stability	Stable			
Conditions to Avoid	Keep away from heat, sparks and flame.			
Incompatible materials	Combustible material (eg. Cotton)			
Hazardous Decomposition Products	No information available.			
	11. Toxicological Information			
Health Effects	Studies have not been performed on this particular mixture. The			
	information below is based on data on the individual ingredients.			
Oral	Expected to be greater than 2,000 mg/kg (rats)			
Ingestion	Nausea, vomiting and abdominal pain.			
Inhalation	Do not spray apply!			
Dermal	May cause irritation			
Eye Effects	May cause irritation			
	12. Ecological Information			
Toxicity:	Very toxic to aquatic organisms.			
Aquatic toxicity	Very toxic to aquatic organisms.			
Persistence and degradability	A mixture of biodegradable and non biodegrable ingredients. No other			
	information is available.			
Bio accumulative potential	Not expected to bioaccumulate significantly.			
	The product has poor water-solubility.			
Mobility in soil	The product has poor water-solubility.			
Mobility in soil Additional ecological information	The product has poor water-solubility. No information available.			

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Contact specialist disposal companies. Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

Item Numbers: 01597-1193, 01597-1192 Page 4 of 6



MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING MERCURY COMPOUND

HAR1490- A June 1, 2015 Page 5 of 6

14. Transport Information

The following transportation categories do not apply to this mixture sold as a consumer use product (non-bulk). The data below refers to the major component of the formulation, Mercury sulfide.

DOT Non-Bulk

Shipping Name Mercury compound, n.o.s. (Mercury Sulfide) **Technical Shipping Name** Mercury compound, n.o.s. (Mercury Sulfide)

Hazard Class 6.1 Poisonous material

UN Number UN 2025

Ш **Packing Group**

IMDG

Shipping Name Mercury compound, n.o.s. (Mercury Sulfide) **Technical Shipping Name** Mercury compound, n.o.s. (Mercury Sulfide)

6.1 Poisonous material **Hazard Class**

UN 2025 UN Number Ш **Packing Group** Marine Pollutant Yes

ICAO/IATA

Shipping Name Mercury compound, n.o.s. (Mercury Sulfide) **Technical Shipping Name** Mercury compound, n.o.s. (Mercury Sulfide)

Hazard Class 6.1 Poisonous material

UN Number UN 2025 **Packing Group** Ш

Michael Harding Art Materials Ltd. are IATA certified through the UK CAA.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the materials.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture.

SARA Not applicable Section 355 (extremely hazardous Not applicable

substances)

Section 313 (Specific toxic chemical listing) Not applicable

TSCA (Toxic Substance Control Act) All ingredients are listed.

The Safe Drinking Water and Toxic As of June 1, 2015 this product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

Enforcement Act of 1986 - California

Proposition 65

Chemicals known to cause cancer None of the ingredients are listed as of 6/1/15. Chemicals known to cause reproductive

toxicity for females

None of the ingredients are listed as of 6/1/15.

Chemicals known to cause reproductive

None of the ingredients are listed as of 6/1/15.

toxicity for males

Page 5 of 6 Item Numbers: 01597-1193 01597-1192



MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING MERCURY COMPOUND

HAR1490- A June 1, 2015 Page 6 of 6

Chemicals known to cause developmental

Mercury sulfide

toxicity

Carcinogenicity categories

EPA (Environmental Protection Agency)

TLV (Threshold Limit Value established by

Not applicable to this mixture.

Not applicable to this mixture.

ACGIH)

MAK (German Maximum Workplace Not applicable to this mixture.

Concentration)

NOISH-Ca (National Institute for Occupational Not applicable to this mixture.

Safety & Health)

OSHA-Ca (Occupational Safety & Health Not applicable to this mixture.

Administration)

16. Other Information

Product Number and Color Name	Pigment Identification
701 Genuine Chinese Vermillion	PR 106 Mercuric Sulphide

Hazard statement(s)

H317 May cause an allergic skin reaction.

Precautionary statement(s)

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/ container to an approved waste disposal plant.

Supersedes MSDS New SDS
Reason for Issue: GHS Format

Prepared by: Rudolph J. Jaeger, Ph.D., DABT, ERT (UK)

Chief Toxicologist and President ENVIRONMENTAL MEDICINE, INC.

263 CENTER AVENUE WESTWOOD, NJ 07675 jaegerr@envmed.com 201-666-7929 x13

The information contained in this Safety Data Sheet was compiled using the latest and most reliable information available to Michael Harding Art Materials, Ltd. The information is provided without any warranty, express or implied regarding its correctness or accuracy nor will Michael Harding Art Materials Ltd. assume any liability for any loss or damage arising out of the use of this information including without limitation direct or indirect losses or expenses. To the extent permitted by law, no warranty express or implied regarding the product described herein shall be created by or inferred from any state or omission for this SDS. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense whatsoever arising out of the product's improper use.

Item Numbers: 01597-1193, 01597-1192 Page 6 of 6