AUXILIARY PRODUCTS

58600 Odourless Thinner

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 1/8

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 58600

Product name AUXILIARY PRODUCTS 58600 Odourless Thinner

Chemical name and synonym Hydrocarbon isoparaffinic

EC number 923-037-2

Registration Number 01-2119471991-29

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Thinner for oil painting.

1.3. Details of the supplier of the safety data sheet

Name INDUSTRIA MAIMERI S.P.A.

Full address Via Gianni Maimeri, 1

District and Country 20060 Mediglia (MI)

Italia

Tel. +39 02 906981 Fax +39 02 90698999

e-mail address of the competent person

responsible for the Safety Data Sheet schedesicurezza@maimeri.it

Product distribution by INDUSTRIA MAIMERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA

(MI) ITALY

1.4. Emergency telephone number

For urgent inquiries refer to Australia: 131126

USA: 1 800 222 1222

Regno Unito NHS Direct (UK): +44 (0) 845 46 47

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Flam. Liq. 3 H226 Asp. Tox. 1 H304 Aquatic Chronic 4 H413 Note 4

Note P

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols: Xn

R phrases: 10-38-53-65-66

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

@EPY 8.1.21 - SDS 1003

Item Numbers: 01565-1019 Page 1 of 8

AUXILIARY PRODUCTS

58600 Odourless Thinner

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 2/8

SECTION 2. Hazards identification. .../>>

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour.

May be fatal if swallowed and enters airways. H304 H413 May cause long lasting harmful effects to aquatic life. **EUH066** Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.

P233

Keep container tightly closed. Ground / bond container and receiving equipment. P240

P241 Use explosion-proof electrical / ventilating / lighting / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge

P280 Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. P301+P310

P303+P361+P353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P331 DO NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice / attention. P370+P378 In case of fire: Use CO2, powder for extinction.

P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

P501 Dispose of contents / container to in accordance with local and national norms. . .

923-037-2 Nr. EC:

2.3. Other hazards.

Information not available.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Contains:

Identification. Conc. %. Classification 67/548/EEC. Classification 1272/2008 (CLP).

ISOPARAFFINIC HYDROCARBON

R10, R53, R66, Xn R65, Xi R38, Note 4 P Flam. Liq. 3 H226, Asp. Tox. 1 H304, Aquatic Chronic 4 H413, EUH066, Note 4 P CAS. 100

EC. 923-037-2 INDEX.

Rea. no. 01-2119471991-29

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

= Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

3.2. Mixtures.

Information not relevant.

Page 2 of 8 Item Numbers: 01565-1019

AUXILIARY PRODUCTS

58600 Odourless Thinner

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 3/8

SECTION 4. First aid measures.

4.1. Description of first aid measures.

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person.

EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed.

No episodes of damage to health ascribable to the product have been reported.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10.

Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering

Page 3 of 8 Item Numbers: 01565-1019

AUXILIARY PRODUCTS

58600 Odourless Thinner

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 4/8

SECTION 7. Handling and storage.

places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

United Kingdom

EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended). Code of Practice Chemical Agent Regulations 2011.

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

OEL EU

TLV-ACGIH ACGIH 2012

ISOPARAFFINIC HYDROCARBON						
Threshold Limit Value.						
Туре	Country	TWA/8h		STEL/15	STEL/15min	
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	1200	196			

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitryl or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of

EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

liquid Appearance Colour colourless

Page 4 of 8 Item Numbers: 01565-1019

AUXILIARY PRODUCTS

58600 Odourless Thinner

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 5 / 8

SECTION 9. Physical and chemical properties. .../>>

Odour characteristic Odour threshold. Not available. Melting point / freezing point. Not available. Initial boiling point. Not available. Boiling range. Not available. Flash point. 23 Not available. **Evaporation Rate** Flammability of solids and gases Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. 0,700 Kg/l Solubility Not available. Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available. Viscosity Not available Explosive properties Not available. Oxidising properties Not available.

9.2. Other information.

VOC (Directive 1999/13/EC): 100,00 % - 700,00 g/litre.

VOC (volatile carbon):

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

ISOPARAFFINIC HYDROCARBON

SECTION 12. Ecological information.

This product may damage the structure and/or the functions of the aquatic ecosystems in the long and/or delayed term.

12.1. Toxicity.

Item Numbers: 01565-1019 Page 5 of 8

AUXILIARY PRODUCTS

58600 Odourless Thinner

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 6 / 8

SECTION 12. Ecological information. .../>>

ISOPARAFFINIC HYDROCARBON

 LC50 (96h) - for Fish.
 1000 mg/l Pesce

 EC50 (48h) - for Algae / Aquatic Plants.
 1000 mg/l Daphnia

 EC50 (72h) - for Crustacea.
 1000 mg/l Alga

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

Road and rail transport:

ADR/RID Class: 3 UN: 3295

Packing Group: III
Label: 3
Nr. Kemler: 30
Limited Quantity. 5 L
Tunnel restriction code. (D/E)

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S.



IMO Class: 3 UN: 3295

Packing Group: III
Label: 3
EMS: F-E, S-D
Marine Pollutant. NO

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S.





Page 6 of 8

AUXILIARY PRODUCTS

58600 Odourless Thinner

Maximum quantity:

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 7/8

SECTION 14. Transport information. .../>>

Transport by air:

Packaging instructions:

UN: 3295 IATA:

Packing Group: Ш Label

Cargo:

Pass. Packaging instructions: 355 Maximum quantity: 60 L

Special Instructions: A3, A224

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S.

366

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point.

Substances in Candidate List (Art. 59 REACH).

Substances subject to authorisarion (Annex XIV REACH).

Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008:

None

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Product not intended for uses provided for by Dir. 2004/42/CE.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Lig. 3 Flammable liquid, category 3 Asp. Tox. 1 Aquatic Chronic 4 Aspiration hazard, category 1

Hazardous to the aquatic environment, chronic toxicity, category 4

H226

Flammable liquid and vapour. May be fatal if swallowed and enters airways. H304 May cause long lasting harmful effects to aquatic life. Repeated exposure may cause skin dryness or cracking **EUH066**

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10 FLAMMABLE.

IRRITATING TO SKIN. **R38**

R53 MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. **R65**

HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED. REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING. **R66**

AUXILIARY PRODUCTS

58600 Odourless Thinner

Revision nr.74 Dated 3/9/2014 Printed on 3/9/2014 Page n. 8 / 8

SECTION 16. Other information. .../>>

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. The Merck Index. 10th Edition
- 9. Handling Chemical Safety
- 10. Niosh Registry of Toxic Effects of Chemical Substances
- 11. INRS Fiche Toxicologique (toxicological sheet)
- 12. Patty Industrial Hygiene and Toxicology
- 13. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 14. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.