

00317-0030**MATERIAL SAFETY DATA SHEET****MSDS #: 559**

Page 1 of 3

Chartpak, Inc.
One River Road
Leeds, MA 01053
Phone: 413-584-5446 or 800-628-1910

Emergency Medical Number: 888-786-0972

Creation Date: April 1, 2007

Section One: Product Information

Product Name: Miskit Liquid Frisket
Product Sizes: 35 ml
Product Class: Mediums

Section Two: Ingredients

Ingredients	CAS Number	% by Weight	PEL/TLV
Natural Rubber Latex	9006-04-6	80.0%	N/A

Section Three: Hazards Identification

WARNING: EXPOSURE MAY CAUSE ALLERGIC REACTIONS, OR HARM TO THE DEVELOPING FETUS. EXPOSURE MAY RESULT IN DIFFICULTY WITH REPRODUCTION (CHILD BEARING). EXPOSURE MAY CAUSE DAMAGE TO THE TESTES OR DIFFICULTY WITH REPRODUCTION (CHILD BEARING), OR DAMAGE TO THE NERVOUS SYSTEM.

CONTAINS: NATURAL RUBBER LATEX, TETRAMETHYL THIURAM DISULFIDE.

Section Four: First Aid Measures

Inhalation: Remove to fresh air.

Skin Contact: Wash with soap and water.

Eye Contact: Flush with flowing water.

Ingestion: Consult a physician. For further health information, contact a poison control center

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 559

MATERIAL SAFETY DATA SHEET

MSDS #: 559

Page 2 of 3

Section Five: Fire Fighting Measures

Flash Point: Not flammable

Flammability Limits (% by volume): Lower: Not explosive Upper: Not explosive

Extinguishing Media: Carbon dioxide, dry chemical, alcohol, or foam

Special Fire Fighting Measures: No special fire fighting procedures.

Unusual Fire and Explosion Hazards: Dried form will support combustion.

Section Six: Accidental Release Measures

Neutralize with acid. Mop off with water. If dried, peel off.

Section Seven: Handling and Storage

Handling: Do not use if allergic to natural rubber latex.

Storage: Store at room temperature.

Section Eight: Exposure Controls and Personal Protection

Respiratory Protection and Special Ventilation Requirements: None required

Other Protective Equipment (Gloves, Goggles, Etc.): Gloves, eye protection, and apron are recommended.

Work/Hygiene Practices: PRECAUTIONS: Wash hands immediately after use. When using, do not eat, drink, or smoke. Wear a work apron. AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Do not use if allergic to natural rubber latex. Not for use by children.

Section Nine: Physical and Chemical Properties

Boiling Point: Not determined Melting Point: Not determined

Vapor Pressure: Not determined Specific Gravity: 0.95

Specific Vapor Density (AIR = 1): Heavier than air Evaporation Rate (Butyl Acetate = 1): Slower

Solubility in Water: Negligible Reactivity in Water: Non-reactive

Appearance and Odor: Milky latex; slight odor

Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Freezing and boiling temperatures

Chemical Incompatibility: Heavy metal ions or acids will cause coagulation

Hazardous Decomposition: Oxides of carbon

Hazardous Polymerization: Will not occur

MATERIAL SAFETY DATA SHEET

MSDS #: 559

Page 3 of 3

Section Eleven: Toxicological Information

IARC Monographs: No
 National Toxicology Program: No
 OSHA Regulated: No

Effects/Symptoms of Acute Exposure: Irritating to the mucous membranes and eye irritation.

Effects/Symptoms of Chronic Exposure: Allergic reactions and difficulty in child bearing

Medical Conditions Usually Aggravated By Overexposure of This Product: Unknown

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen: Transport Information

Not regulated as a hazardous material by DOT, IMO, or IATA.

Section Fifteen: Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen: Other Information

HMIS Code	
Health	2
Flammability	1
Reactivity	0
Personal Protection	C

Chartpak, Inc. is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.